

L MATERIAL SAFETY DATA SHEET

# S-OIL SEVEN GEAR TO-4 40

Date of the previous version: 2018-03-14

Revision Date: 2018-03-14

Version 1

# **1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

#### **1.1. Product identifier**

Product nameS-OIL SEVEN GEAR TO-4 40Pure substance/mixtureMixture

#### **1.2. Relevant identified uses of the substance or mixture and uses advised against**

Recommended Use

Engine Oil.

#### 1.3. Details of the supplier of the safety data sheet

Manufacturer

S-OIL CORPORATION 192, Baekbeom-ro, Mapo-gu, Seoul 121-805, Korea

For further information, please contact:

Contact Point E-mail Address

#### **1.4. Emergency telephone number**

Korea

+82 2 6320 2000

#### 2. HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

Classification Serious eye damage/eye irritation : Category 2 Skin sensitization : Category 1

Symbol(s)



#### **2.2. Label elements**

Signal word

Warning

#### 2.3. hazards Statement

H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H412	Harmful to aquatic life with long lasting effects

# **2.4. Precautionary Statements**

P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash the hands thoroughly after handling.



S-OIL SEVEN GEAR TO-4 40

Date of the previous version: 2018-03-14	Revision Date: 2018-03-14	Version 1
P272 P273 P280	Contaminated work clothing should not be allowed out of the Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/fa	
P305+P351+P338 P302+P352 P333+P313 P337+P313 P308+P313 P321 P363	IF IN EYES: Rinse cautiously with water for several m contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Wash contaminated clothing before reuse.	
P501	Dispose of contents/container to (in accordance with lo national / International regulation)	ocal / regional /
2.5. Other hazards		
Physical-Chemical Properties	Contaminated surfaces will be extremely slippery.	
Environmental properties	Should not be released into the environment.	

## **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1. Mixture

Chemical Name	CAS-No	EC-No	Weight %
Severely hydrogenated heavy paraffinic distillate	64742-54-7	-	80.0 ~ 85.0
Residual oils (Petroleum), Hydrotreated	64742-57-0	-	10.0 ~ 15.0
Mixed Performance Additive	Mixture	-	5.0 ~ 10.0
Pour point depressant	Mixture	-	< 1.0
Hazardous ingredients Do not contain hazardous substance nor substance with European workplace   exposure limits in concentration above regulatory thresholds			
Additional information Product containing mineral oil with less than 3% DMSO extract as measured by IP 346			

# **4. FIRST AID MEASURES**

## **4.1. Description of first-aid measures**

General advice	IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids.
Skin contact	Remove contaminated clothing and shoes. Wash skin with soap and water. Wash contaminated clothing before reuse. High pressure jets may cause skin damage. In this case, the casualty should be sent immediately to hospital.
Inhalation	Move to fresh air.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.

# 4.2. Most important symptoms and effects, both acute and delayed



-OIL MATERIAL SAFETY DATA SHEET

# S-OIL SEVEN GEAR TO-4 40

Date of the previous version	<b>1:</b> 2018-03-14	Revision Date: 2018-03-14	Version 1
Eye contact	Not classified.		
Skin contact		gh pressure injection of the products under the sense even though no symptom or injury may be	
Inhalation	Not classified. Inl respiratory system	nalation of vapors in high concentration may cau m.	use irritation of
Ingestion	Not classified. Ing diarrhea.	gestion may cause gastrointestinal irritation, nat	usea, vomiting and
4.3. Indication of imm	ediate medical att	ention and special treatment need	led, if necessary

Notes to physician	
--------------------	--

#### Treat symptomatically.

# **5. FIRE-FIGHTING MEASURES**

## 5.1. Extinguishing media

Suitable extinguishing media	Carbon dioxide (CO 2). ABC powder. Foam. Water spray or fog.
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire.

#### 5.2. Special hazards arising from the substance or mixture

Special Hazard	Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These maybe highly dangerous if inhaled in confined spaces or at high concentration.
5.3. Advice for fire-fighters	<u>5</u>
Special protective equipment for fire-fighters	Wear self-contained breathing apparatus and protective suit.
Other information	Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

# 6. ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

General Information	Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all
	sources of ignition.

## **6.2. Environmental precautions**

General Information	Do not allow material to contaminate ground water system. Try to prevent the material from
	courses. Local authorities should be advised if significant spillages cannot be contained.

#### 6.3. Methods and material for containment and cleaning up

Methods for containment	Dam up. Contain spillage, and then collect with non-combustible absorbent material, (e.g.
	sand, earth, diatomaceous earth, vermiculite) and place in container for disposal
	according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.



L MATERIAL SAFETY DATA SHEET

# S-OIL SEVEN GEAR TO-4 40

Date of the previous version: 2018-03-14

Revision Date: 2018-03-14

Version 1

## 6.4. Reference to other sections

Personal Protective EquipmentSee Section 8 for more detail.Waste treatmentSee section 13.

#### 7. HANDLING AND STORAGE

#### 7.1. Precautions for safe handling

Advice on safe handling	When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.
Prevention of fire and explosion	Take precautionary measures against static discharges. Ground/bond containers, tanks and transfer/receiving equipment.
Hygiene measures	Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.
7.2. Conditions for safe ste	orage, including any incompatibilities

**Technical measures/Storage conditions** Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture.

Materials to Avoid Strong oxidizing agents.

#### 7.3. Specific end uses

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

Exposure limits	Oil mist : TWA 5mg/m <sup>3</sup> (8hr), STEL 10mg/m <sup>3</sup> (15min).
Legend	See section 16.
8.2. Exposure controls	
Occupational Exposure Controls	
Engineering Measures	Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.
Personal Protective Equipment	
General Information	If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.



MATERIAL SAFETY DATA SHEET

# S-OIL SEVEN GEAR TO-4 40

Date of the previous version: 2018-03-14 Revision Date: 2018-03-14 Version 1 None under normal use conditions. When workers are facing concentrations above the **Respiratory protection** exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387). The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses. **Eye Protection** If splashes are likely to occur, wear:. Safety glasses with side-shields. Skin and body protection Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing. **Hand Protection** Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves. **Environmental exposure controls** 

#### **General Information**

The product should not be allowed to enter drains, water courses or the soil.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. Information on basic physical and chemical properties

Color Physical State @20°C Odor		Yellow to amber liquid Characteristic	
<u>Property</u> pH Boiling point/boiling range	<u>Values</u>	<u>Remarks</u> Not applicable Not applicable	<u>Method</u>
Flash point Evaporation rate Flammability Limits in Air Vapor Pressure Vapor density Density Water solubility Solubility in other solvents logPow Autoignition temperature Viscosity, kinematic Explosive properties Oxidizing Properties Possibility of hazardous reactions	262 °C 897kg/m3 144.5mm <sup>2</sup> /s 14.42 mm <sup>2</sup> /s Not explosive Not applicable Not applicable	No information available No information available No information available No information available @ 15 °C Soluble No information available No information available No information available @ 40 °C @ 100 °C	Cleveland Open Cup (COC)

#### 9.2. Other information

**Other Information** 

No information available.

# **10. STABILITY AND REACTIVITY**

#### 10.1. Reactivity

**General Information** 

No information available.



OIL MATERIAL SAFETY DATA SHEET

# S-OIL SEVEN GEAR TO-4 40

Date of the previous version: 2018-03-14

Revision Date: 2018-03-14

Version 1

# 10.2. Chemical stability

Stability Stable under recommended storage conditions.

## **10.3. Possibility of hazardous reactions**

Hazardous Reactions None under normal processing.

## 10.4. Conditions to Avoid

Conditions to Avoid Heat (temperatures above flash point), sparks, ignition points, flames, static electricity.)

## **10.5. Incompatible Materials**

Materials to Avoid Strong oxidizing agents.

# **10.6. Hazardous Decomposition Products**

Hazardous Decomposition	CO, CO <sub>2</sub> , Carbon oxide.
Product	

# **11. TOXICOLOGICAL INFORMATION**

#### **11.1. Information on toxicological effects**

#### Acute toxicity Local effects Product Information

Skin contact	. Not classified. High pressure injection of the products under the skin may have very serious consequences even though no symptom or injury may be apparent.
Eye contact	. Not classified.
Inhalation	. Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system
Ingestion	. Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

#### Acute toxicity- Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Severely hydrogenated heavy	LD50 > 15000mg/kg	LD50 > 5000mg/kg	-
paraffinic distillate	(Rat)	(Rabbit)	

## Sensitization

Chemical Name	Sensitization
Mixed Performance Additive	Eye : Contact with the eyes causes permanent damage, including blindness. Symptoms may include pain, tearing, reddening, swelling and impaired vision. If this material is heated, thermal burns may result from eye contact.
Mixed Performance Additive	Skin : Repeated contact with the skin may cause irritation. Symptoms may include pain, itching, discoloration, swelling, and blistering. Contact with the skin is not expected to cause an allergic skin response. Not expected to be harmful to internal organs if absorbed through the skin. If this material is heated, thermal burns may result from skin contact.



OIL MATERIAL SAFETY DATA SHEET

# S-OIL SEVEN GEAR TO-4 40

Date of the previous version: 2018-03-14

Revision Date: 2018-03-14

Version 1

#### Specific effects

Carcinogenicity	This product is not classified carcinogenic.
Mutagenicity	This product is not classified as mutagenic.
Reproductive toxicity	This product does not present any known or suspected reproductive hazards.

Chemical Name	Reproductive toxicity	
Mixed Performance Additive	Contains material that may cause adverse reproductive effects upon repeated swallowing based on animal data. The hazard evaluation is based on data for components or a similar material.	
Repeated Dose Toxicity		
Subchronic toxicity	No information available.	
Target Organ Effects (STOT)		
Target Organ Effects (STOT)	No information available.	
Other information		
Other adverse effects	Characteristic skin lesions (pimples) may develop following prolonged and repeate exposures (contact with contaminated clothing).	

# **12. ECOLOGICAL INFORMATION**

#### 12.1. Toxicity

#### Aquatic toxicity - Product Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates.	Toxicity to fish
Severely hydrogenated heavy paraffinic distillate	LC50 >1000mg/L 96hr	LC50 >1000mg/L 48hr	LC50 >1000mg/L 96hr

#### Effects on terrestrial organisms

No information available.

#### **General Information**

No information available.

## **12.2. Persistence and degradability**

#### **General Information**

Persistence	No information available.

degradability No information available.

# **General Information**

No information available.

# **12.3. Bioaccumulative potential**

#### **Product Information**

Chemical Name Biodegradability	Chemical Name	Biodegradability
--------------------------------	---------------	------------------



L MATERIAL SAFETY DATA SHEET

# S-OIL SEVEN GEAR TO-4 40

Date of the previous version: 2018-03-14

Revision Date: 2018-03-14

Version 1

Severely hydrogenated heavy paraffinic distillate 6% (28days)

<u>logPow</u>

# 12.4. Mobility in soil

Soil	Given its physical and chemical characteristics, the product generally shows low soil mobility.
Air	Loss by evaporation is limited.
Water	Soluble.

# 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** No information available.

#### 12.6. Other adverse effects

General Information

No information available

## **13. DISPOSAL CONSIDERATIONS**

#### **13.1. Waste treatment methods**

Waste from Residues / Unused Products	Should not be released into the environment. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.
EWC Waste Disposal No.	The following Waste Codes are only suggestions:. 13 01 10. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

14. TRANSPORT INFORMATION			
ADR/RID	Not regulated		
IMDG/IMO	Not regulated		
ICAO/IATA	Not regulated		
ADN	Not regulated		

# **15. REGULATORY INFORMATION**

# **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

#### **European Union**

**International Inventories** 



MATERIAL SAFETY DATA SHEET

# S-OIL SEVEN GEAR TO-4 40

Date of the previous version: 2018-03-14

Revision Date: 2018-03-14

Skin designation

Trade secret

Carcinogen

Version 1

No information available

#### **Further information**

#### **15.2. Chemical Safety Assessment**

Chemical Safety Assessment No information available

#### **16. OTHER INFORMATION**

#### Abbreviations, acronyms

Legend Section 8

+ ** M:	Sensitizer Hazard Designatior Mutagen	ı	* *** : C:	
Revision Date:		018-03-14	 	

**Revision Note** \*\*\* Indicates updated section.

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by theuser that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the safety data sheet