

S-OIL TURBINE

SYNTHETIC INDUSTRIAL TURBINE OIL

Product Description

S-OIL TURBINE is high quality turbine oil designed for steam or hydraulic turbine operating under all service conditions. It made from advanced additive technology and pure base oil produced through severe hydrocracking process, so excellent oxidation and thermal stability can help your machine can operate longer and more stable and the maintenance cost could be reduced.

Applications

O Steam & Hydraulic turbines operating under all service conditions

Features and potential benefits

- O Good anti-foam performance for equipment trouble control
- O Good filterability even in the presence of water
- O Environmental friendly formulation with ashless additive technology
- O Excellent protection against rust and corrosion
- O Good demulsibility ensuring rapid water separation
- O Reduced maintenance costs due to high oxidation and thermal stability
- O Good resistance to oxidation avoiding formation of sludge at normal operation temperature and ensuring a long service life of the fluid thanks to high quality synthetic base oil

Performance level

O DIN 51515, PART I (L-TD), PART II (L-TG)	O CEGB Standard 207001
O Siemens TLV 9013 04/01	O Brown Boveri HTGD 90117
O British Standard BS489	• U.S.Steel 120
O General Electric GEK 32568 A/C	O Westinghouse Electric Corp
O MIL-L-17672D/17672D	O Alstom HTGD 90 117 V0001 S
 O British Standard BS489 O General Electric GEK 32568 A/C 	O U.S.Steel 120O Westinghouse Electric Corp

Typical Properties

Test	ltems	Method	Unit	Full Synthetic ISO VG 32	Synthetic Blended ISO VG 46
Specific grav	rity	ASTM D1298	-	0.8421	0.8477
Color		ASTM D1500	-	L 1.0	L 1.0
Viscosity	40° C	ASTM D445	cSt	33.21	46.52
	100° C	ASTM D445	cSt	5.80	7.77
Viscosity index		ASTM D2270	-	129	129
Water Seperability		ASTM D1401	Min	7	8
Flash point		ASTM D92	°C	242	245
Pour point		ASTM D97	°C	-37	-31

S-OIL CORPORATION 192, Baekbeom-ro, Mapo-gu, Seoul, 04196, Korea

S-OIL TURBINE 2018.3.12.



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.