

# MATERIAL SAFETY DATA SHEET

## DRAGON 2T MOTOR OIL

Date of the previous version: 2015-07-07

Revision Date: 2015-07-07

Version 1

### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name DRAGON 2T MOTOR OIL  
Pure substance/mixture Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use 2 Stroke motorcycle engine oil

#### 1.3. Details of the supplier of the safety data sheet

Supplier S-OIL CORPORATION  
192, Baekbeom-ro, Mapo-gu,  
Seoul 121-805, Korea

For further information, please contact:

#### 1.4. Emergency telephone number

Korea + 82 2 3772-5733

### 2. HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

GHS Classification

Skin corrosion/irritation : Category 2  
Carcinogenicity : Category 2

#### 2.2. Label elements

GHS label elements, including precautionary statements

Symbol(s)



Signal Words

Danger

#### 2.3. GHS Precautionary Statements

Hazard

H315 Causes skin irritation  
H351 Suspected of causing cancer

Prevention & Response

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P281 Use personal protective equipment as required.

**MATERIAL SAFETY DATA SHEET****DRAGON 2T MOTOR OIL**

Date of the previous version: 2015-07-07

Revision Date: 2015-07-07

Version 1

P264 Wash your hand thoroughly after handling.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+313 IF exposed or concerned: Get medical advice/attention.  
P302+352 IF ON SKIN: Wash with plenty of soap and water.  
P321 Specific treatment  
P332+313 If skin irritation occurs: Get medical advice/attention.  
P362 Take off contaminated clothing and wash before reuse.

**Storage**

P405 Store locked up.

**Disposal**

P501 Dispose of contents/container to follow the related law

**2.4. Other hazards**

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.

Environmental properties Should not be released into the environment

**3. COMPOSITION/INFORMATION ON INGREDIENTS****3.2. Mixture**

Chemical Name	CAS-No	EC-No	Weight %
SEVERELY HYDROTREATED HEAVY PARAFFINIC DISTILLATE	64742-54-7	265-157-1	70.0 ~ 73.0
KEROSENE	8008-20-6	-	15.0 ~ 20.0
POLYISOBUTYLEN	9003 - 27 -4	-	7.0 ~ 13.0
MIXED PERFORMANCE ADDITIVE	Mixture	-	< 4

Additional information Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

**4. FIRST AID MEASURES****4.1. Description of first-aid measures**

**General advice** IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

**Eye contact** Rinse thoroughly with plenty of water, also under the eyelids.

**Skin contact** Remove contaminated clothing and shoes. Wash skin with soap and water. Wash contaminated clothing before reuse.  
High pressure jets may cause skin damage. In this case, the casualty should be sent immediately to hospital.

**Inhalation** Move to fresh air.

**Ingestion** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.



## MATERIAL SAFETY DATA SHEET

### DRAGON 2T MOTOR OIL

Date of the previous version: 2015-07-07

Revision Date: 2015-07-07

Version 1

material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

#### **6.4. Reference to other sections**

Personal Protective Equipment	See Section 8 for more detail.
Waste treatment	See section 13.

### **7. HANDLING AND STORAGE**

#### **7.1. Precautions for safe handling**

Advice on safe handling	When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.
Prevention of fire and explosion	Take precautionary measures against static discharges. Ground/bond containers, tanks and transfer/receiving equipment.
Hygiene measures	Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

#### **7.2. Conditions for safe storage, including any incompatibilities**

Technical measures/Storage conditions	Keep away from food, drink and animal feeding stuffs. Keep in a bunded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture.
Materials to Avoid	Strong oxidizing agents.

#### **7.3. Specific end uses**

### **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### **8.1. Control parameters**

Exposure limits	oil mist : 10mg/m <sup>3</sup> , for 15 minutes; oil mist : 5mg/m <sup>3</sup> , for 8 hours
Legend	See section 16.

#### **8.2. Exposure controls**

##### **Occupational Exposure Controls**

Engineering Measures	Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.
----------------------	--

## MATERIAL SAFETY DATA SHEET

### DRAGON 2T MOTOR OIL

Date of the previous version: 2015-07-07

Revision Date: 2015-07-07

Version 1

#### Personal Protective Equipment

<b>General Information</b>	If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.
<b>Respiratory protection</b>	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387). The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.
<b>Eye Protection</b>	If splashes are likely to occur, wear: Safety glasses with side-shields.
<b>Skin and body protection</b>	Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing.
<b>Hand Protection</b>	Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves.

#### Environmental exposure controls

**General Information** The product should not be allowed to enter drains, water courses or the soil.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### **9.1. Information on basic physical and chemical properties**

Color		Dark blue	
Physical State @20°C		liquid	
Color		Characteristic	
<b><u>Property</u></b>	<b><u>Values</u></b>	<b><u>Remarks</u></b>	<b><u>Method</u></b>
pH		Not applicable	
Boiling point/boiling range		Not applicable	
Flash point	114 °C 237 °F		Cleveland Open Cup (COC) Cleveland Open Cup (COC)
Evaporation rate		No information available	
Flammability Limits in Air		No information available	
Vapor Pressure		No information available	
Vapor density		No information available	
Density	873 kg/m <sup>3</sup>	@ 15 °C	
Water solubility	Negligible	Insoluble	
Solubility in other solvents		No information available	
logPow		No information available	
Autoignition temperature		No information available	
Viscosity, kinematic	7.87 mm <sup>2</sup> /s	@ 100 °C	
Explosive properties	Not explosive		
Oxidizing Properties	Not applicable		
Possibility of hazardous reactions	Not applicable		

#### **9.2. Other information**

### 10. STABILITY AND REACTIVITY

## MATERIAL SAFETY DATA SHEET

### DRAGON 2T MOTOR OIL

Date of the previous version: 2015-07-07

Revision Date: 2015-07-07

Version 1

#### **10.1. Reactivity**

General Information No information available.

#### **10.2. Chemical stability**

Stability. Stable under recommended storage conditions.

#### **10.3. Possibility of hazardous reactions**

Hazardous Reactions None under normal processing.

#### **10.4. Conditions to Avoid**

Conditions to Avoid Heat (temperatures above flash point), sparks, ignition points, flames, static electricity.

#### **10.5. Incompatible Materials**

Materials to Avoid Strong oxidizing agents.

#### **10.6. Hazardous Decomposition Products**

Hazardous Decomposition Product None under normal use.

### **11. TOXICOLOGICAL INFORMATION**

#### **11.1. Information on toxicological effects**

##### **Acute toxicity Local effects Product Information**

**Skin contact** . Not classified. High pressure injection of the products under the skin may have very serious consequences even though no symptom or injury may be apparent.

**Eye contact** . Not classified.

**Inhalation** . Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.

**Ingestion** . LD50 > 5000mg/kg (Rat, Oral), Practically non-toxic.  
 . LD50 > 5000mg/kg (Rabbit, Dermal), Practically non-toxic.

##### **Acute toxicity - Component Information**

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
SEVERELY HYDROTREATED HEAVY PARAFFINIC DISTILLATE	LD50 > 5,000mg/kg (Rat)	LD50 > 5,000mg/kg (Rabbit)	
KEROSENE	LD50 2,835mg/kg (Rabbit)	LD50 > 2,000mg/kg (Rabbit)	LC50 > 5.28mg/L (4hr, Rat)

#### **Sensitization**

Sensitization

## MATERIAL SAFETY DATA SHEET

### DRAGON 2T MOTOR OIL

Date of the previous version: 2015-07-07

Revision Date: 2015-07-07

Version 1

Chemical Name	Sensitization
KEROSENE	Irritation on the skin of human

**Specific effects**

**Carcinogenicity**

Chemical Name	Carcinogenicity
KEROSENE	ACGIH : A3 (Animal carcinogen)

**Mutagenicity**

This product is not classified as mutagenic.

**Reproductive toxicity**

This product does not present any known or suspected reproductive hazards.

**Repeated Dose Toxicity**

**Subchronic toxicity**

No information available.

**Target Organ Effects (STOT)**

**Target Organ Effects (STOT)**

No information available.

**Other information**

**Other adverse effects**

Characteristic skin lesions (pimples) may develop following prolonged and repeated exposures (contact with contaminated clothing).

## 12. ECOLOGICAL INFORMATION

### **12.1. Toxicity**

**Acute aquatic toxicity - Product Information**

No information available.

**Acute aquatic toxicity - Component Information**

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates.	Toxicity to fish	Toxicity to microorganisms
KEROSENE			LC50 5mg/L 96hr	

**Chronic aquatic toxicity - Product Information**

No information available.

**Chronic aquatic toxicity - Component Information**

No information available.

**Effects on terrestrial organisms** No information available.

### **12.2. Persistence and degradability**

**General Information**

No information available.

### **12.3. Bioaccumulative potential**

**Product Information**

No information available.

**logPow**

No information available

**MATERIAL SAFETY DATA SHEET****DRAGON 2T MOTOR OIL**

Date of the previous version: 2015-07-07

Revision Date: 2015-07-07

Version 1

Component Information No information available.

**12.4. Mobility in soil**

Soil Given its physical and chemical characteristics, the product generally shows low soil mobility.

Air Loss by evaporation is limited.

Water Insoluble. The product spreads on the surface of the water.

**12.5. Results of PBT and vPvB assessment**

PBT and vPvB assessment No information available.

**12.6. Other adverse effects**

General Information No information available

**13. DISPOSAL CONSIDERATIONS****13.1. Waste treatment methods**

Waste from Residues / Unused Products Should not be released into the environment. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

EWC Waste Disposal No. The following Waste Codes are only suggestions: 13 01 10. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

**14. TRANSPORT INFORMATION****ADR/RID** Not regulated**IMDG/IMO** Not regulated**ICAO/IATA** Not regulated**ADN** Not regulated**15. REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****International Inventories**EINECS/ELINCS  
TSCA



## MATERIAL SAFETY DATA SHEET

### DRAGON 2T MOTOR OIL

Date of the previous version: 2015-07-07

Revision Date: 2015-07-07

Version 1

**KECL****Legend**

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

KECL - Korean Existing and Evaluated Chemical Substances

**Further information****15.2. Chemical Safety Assessment**

Chemical Safety Assessment      No information available

**16. OTHER INFORMATION****Abbreviations, acronyms**

Legend Section 8

+	Sensitizer	*	Skin designation
**	Hazard Designation	C:	Carcinogen
M:	Mutagen	R:	Toxic to reproduction

Revision Date: 2015-07-07

Revision Note      \*\*\* Indicates updated section.

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the safety data sheet