



Product Description

S-OIL DRAGON CJ-4/SL is made by synthetic technology, suitable for all heavy-duty engines, non turbo-charged or turbo-charged, in on and off-highway service. And recommended for vehicles fitted with after treatment devices including diesel particulate filters (DPFs)

Applications

- O All turbocharged or normally aspirated diesel engines of vehicles operating in the most severe conditions
- O Light trucks, RVs, SUVs, Heavy trucks, Buses with diesel engines
- O Especially diesel vehicles with European engine under high pressure and temperature
- Particularly suited for EURO VI, V, IV to older generation engines fitted with after treatment devices including DPF, EGR and SCR

Features and potential benefits

- O This low SAPS (Sulfated Ash, phosphorus, sulfur) engine oil provides long life for exhaust after treatment devices including diesel particulate filter
- O Synthetic technology enhances the engine protection and engine oil life thanks to high stability and cleanliness
- O Excellent detergent system helps keep pistons and other engine parts clean for long engine life
- O Good thermal breakdown resistance ensures engine protection under modern engine's severe conditions
- O In cold condition, Good fluidity provides easy start and prevents wear damage in initial stage

Performance level

O API : API CJ-4/SL

Typical Properties

Test Items		Method	Unit	10W-40	15W-40
Specific gravity		ASTM D1298	-	0.8644	0.8716
Viscosity	40°C	ASTM D445	cSt	104.4	108.2
	100° C	ASTM D445	cSt	15.41	14.84
Viscosity index		ASTM D2270	-	156	142
Flash point		ASTM D92	°C	224	232
Pour point		ASTM D97	°C	L-40	L-40

S-OIL CORPORATION 192, Baekbeom-ro, Mapo-gu, Seoul, 04196, Korea

S-OIL DRAGON CJ-4/SL 2016.12.13.



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.