



Product Description

DRAGON COMBO BEST is made by synthetic blend technology, suitable for both gasoline and diesel engines (passenger cars and light duty vehicles). DRAGON COMBO BEST can be used in the most severe operating conditions (motorways, dense city traffic), whatever the season.

Applications

- O DRAGON COMBO BEST is perfectly suited to turbo-charged and multi-valve engines.
- O Particularly suited for lubrication of low emission engines.

Features and potential benefits

- O Very high viscosity index and excellent viscosity stability in operation
- O Technology which gives the properties of both fluid oils (easy cold starts) and viscous oils (perfect lubrication at high temperature, low oil consumption)
- O Excellent dispersancy and detergency keeping the engine clean and thus preserving its power
- O Excellent antiwear properties protecting the engine's most sensitive parts.

Performance level

O ACEA: ACEA A3/B3 O API: API CI-4/SL

O OEM Specifications: MB 229.1

Typical Properties

Test Items		Method	Unit	10W-40
Specific gravity		ASTM D1298	-	0.870
Viscosity	40 °C	ASTM D445	cSt	100.7
	100°C	ASTM D445	cSt	15.0
Viscosity index		ASTM D2270	-	160
Flash point		ASTM D92	$^{\circ}$	230
H.T.H.S viscosity		ASTM D4683		4
Pour point		ASTM D97	$^{\circ}$	-35

S-OIL CORPORATION 192, Baekbeom-ro, Mapo-gu, Seoul, 04196, Korea

DRAGON COMBO BEST 2016.12.13.

