

Product Description

DRAGON SF/CF is multi-grade engine oil for all gasoline engines. It suitable for recent technology engines (multi-valve, turbocharged, with/without catalytic converter) and vehicles requiring performance specification API SF/CF

Applications

- All gasoline engines, especially for most recent technology engines (multi-valve, turbocharged, with/without catalytic converter) supercharged or not, in cars
- O Suitable for all journeys (in town, on highways) and particularly in severe conditions
- O For all driving styles, vigorous speeds in all seasons

Features and potential benefits

- O Meets API SF/CF requirements, guarantee of an high and constant quality for lubricants
- O Ensures easy cold start due to its extreme fluidity at low temperature and maintains a very resistant oil film even at extremely high operating temperature
- O Protects mechanical parts and fully preserves the engine power, thus contributing to its youth and strength.

Performance level

O API : API SF/CF

Typical Properties

Test Items		Method	Unit	20W-50
Specific gravity		ASTM D1298	-	0.88
Viscosity	40° C	ASTM D445	cSt	169.9
	100°C	ASTM D445	cSt	19.16
Viscosity index		ASTM D2270	-	128
Flash point		ASTM D92	°C	248
Pour point		ASTM D97	°C	-28

S-OIL CORPORATION 192, Baekbeom-ro, Mapo-gu, Seoul, 04196, Korea

DRAGON SF/CF 2017.09.25.



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.