



Product Description

DRAGON SJ is multi-grade engine oil for all gasoline engines. It suitable for recent technology engines (multivalve, turbocharged, with/without catalytic converter) and vehicles requiring performance specification API SJ

Applications

- O All gasoline engines, especially for most recent technology engines (multi-valve, turbocharged, with/without catalytic converter) supercharged or not, in cars
- O Suitable for all journeys (in town, on highways) and particularly in severe conditions
- For all driving styles, vigorous speeds in all seasons

Features and potential benefits

- O Meets API SJ and ILSAC GF-2(5W-30 and 10W-30) requirements, guarantee of an high and constant quality for lubricants
- O Ensures easy cold start due to its extreme fluidity at low temperature and maintains a very resistant oil film even at extremely high operating temperature
- O Gives the engine an excellent wear protection, develops performance and power.
- O Keeps the engine's most sensitive parts clean thanks to its advanced detergent and dispersive additivities.

Performance level

O API: API SJ

O ILSAC : GF-2 (5W-30, 10W-30)

Typical Properties

Test Items		Method	Unit	5W-30	10W-30	10W-40	20W-50
Specific gravity		ASTM D1298	-	0.8628	0.8692	0.8690	0.8842
Viscosity	40 ℃	ASTM D445	cSt	59.17	66.34	106.9	154.00
	100°C	ASTM D445	cSt	10.20	10.42	15.87	17.32
Viscosity index		ASTM D2270	-	161	145	159	121
Flash point		ASTM D92	$^{\circ}$	222	234	222	252
Pour point		ASTM D97	$^{\circ}$	-40	-40	-38	-25

S-OIL CORPORATION 192, Baekbeom-ro, Mapo-gu, Seoul, 04196, Korea



