



S-OIL dragon SM

MULTI GRADE OIL FOR GASOLINE ENGINE

Product Description

DRAGON SM is multi-grade engine oil for all gasoline engines. It suitable for recent technology engines (multi-valve, turbocharged, with/without catalytic converter) and vehicles requiring performance specification API SM

Applications

- All gasoline engines, especially for most recent technology engines (multi-valve, turbocharged, with/without catalytic converter) supercharged or not, in cars
- Suitable for all journeys (in town, on highways) and particularly in severe conditions
- For all driving styles, vigorous speeds in all seasons

Features and potential benefits

- Meets API SM requirements, guarantee of an high and constant quality for lubricants
- Ensures easy cold start due to its extreme fluidity at low temperature and maintains a very resistant oil film even at extremely high operating temperature
- Protects mechanical parts and fully preserves the engine power, thus contributing to its youth and strength.

Performance level

- API : API SM/CF

Typical Properties

Test Items	Method	Unit	10W-40
Specific gravity	ASTM D1298	-	0.790
Viscosity 40°C	ASTM D445	cSt	99.42
100°C	ASTM D445	cSt	14.62
Viscosity index	ASTM D2270	-	153
Flash point	ASTM D92	°C	234
Pour point	ASTM D97	°C	-37.5

S-OIL CORPORATION
192, Baekbeom-ro, Mapo-gu,
Seoul, 04196, Korea

DRAGON SM
2017.09.25.



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.