

Product Description

DRAGON TURBO BEST is made by synthetic blend technology, suitable for all diesel engines (passenger cars and light heavy duty vehicles). DRAGON TURBO BEST can be used in the most severe operating conditions (motorways, dense city traffic), whatever the season.

Applications

- O DRAGON TURBO BEST is perfectly suited to turbo-charged and multi-valve engines.
- O Particularly suited for lubrication of low emission engines.

Features and potential benefits

- O Formulated with optimized ash contents to prevent wear damage or troubles of valve system
- O Excellent anti oxidation and nitration performance at very high operation temperature of Diesel engine
- O High chemical stability and long drain interval helps the engine stay in good condition during whole period
- O Good fluidity at low temperature, so it secure the excellent cold startability and fewer oil consumption

Performance level

- O API CI-4/SL
- O ACEA E3/E5
- O Volvo VDS-2/3
- O MAN M 3275
- O MB 228.3/229.1

- O CES 20071, 20072, 20076, 20077, 20078
- O Mack EO-M/EO-M Plus
- O Global DHD-1
- O ALLISOON C4

Typical Properties

Test Items		Method	Unit	15W-40
Specific gravity		ASTM D1298	-	0.8603
Viscosity	40° C	ASTM D445	cSt	105.0
	100℃	ASTM D445	cSt	14.83
Viscosity index		ASTM D2270	-	147
Flash point		ASTM D92	°C	224
H.T.H.S viscosity		ASTM D4683		4.1
Pour point		ASTM D97	°C	-35

S-OIL CORPORATION 192, Baekbeom-ro, Mapo-gu, Seoul, 04196, Korea

DRAGON TURBO BEST 2016.12.13.



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.