



S-OIL SEVEN *ATF Multi*

FULLY SYNTHETIC Multi-purpose Automatic Transmission Fluid

Product Description

S-OIL 7 ATF Multi is a premium automatic transmission fluid based on highly refined API Group III base oil and suitable for use in wide range of Asian, European, American vehicles. Its excellent thermal and oxidation stability prevents deposit or corrosive matters in your gear box, so It provides stable operation of your ATF and long oil life.

Applications

- Wide range of 4/5/6/6+ speed automatic gearboxes in Asian, European, American passenger vehicles
- You should follow the vehicle's automatic transmission fluid change interval and performance level recommended in your owner's manual

Features and potential benefits

- Full synthetic base oil* helps maintain oils initial conditions thanks to good stability and high viscosity index
- *) S-OIL manufactures high quality API Group III base oil named "ULTRA-S" and provides it globally
- Exceptional friction and anti-shudder performances with advanced technology
- Excellent viscosity stability in operation
- Excellent thermal stability and resistance to oxidation
- Very good wear protection

Performance level

- GM DEXRON II/IID/IIIE/IIIG/IIIH/VI, Ford Mercon, Allison C4/TES-295/TES-389, Land Rover Texaco N402
- Jaguar Idemitsu K17/Fluid 8432, Chrysler ATF+3/+4/SP-III, Esso LT 71141, JWS 3309
- SSANGYONG DSIH 5M-66, Hyundai Kia SP-II/III/IV/IV-RR, JASO M315 1A
- Toyota Type D-II/T/T-III/T-IV/T-WS, Mitsubishi J2/SP-II/SP-III, Mazda FZ/F-1/JWS3317/M-III/Type T-IV/M-V
- Nissan Matic-D/J/K/W/S, Subaru ATF; plus ATF-HP, Isuzu ATF II/III, Suzuki 3314/3317, Honda ATF Z-1/DW-1
- Volkswagen/Audi G052 025 A2/055/162(-A1/-A2)/533/990(A2)/G055 025(A2)
- BMW LT71141/LA2634/ETL-7045E/8072B, Mercedes Benz 236.3/5/6/7/8/9/10/11/91, Renault Matic-D2
- ZF TE ML 11A/11B, MAN 339A, Bentley, Porsche, PSA, Volvo ATFs

Typical Properties

Test Items	Method	Unit	S-OIL 7 ATF Multi	
Specific gravity	ASTM D1298	-	0.848	
Color	ASTM D1500	-	Red	
Viscosity	40°C	ASTM D445	cSt	36.8
	100°C	ASTM D445	cSt	7.0
Viscosity index	ASTM D2270	-	153	
Flash point	ASTM D92	°C	232	
Pour point	ASTM D97	°C	-46	

S-OIL CORPORATION
192, Baekbeom-ro, Mapo-gu,
Seoul, 04196, Korea

S-OIL 7 ATF Multi
2016.06.23.



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.