



S-OIL SEVEN ATF VI

FULLY SYNTHETIC AUTOMATIC TRANSMISSION FLUID

Product Description

S-OIL SEVEN ATF VI is an innovative automatic transmission fluid based on an advanced synthetic technology allowing very high performance. It offers fuel economies thanks to low viscosity. This lubricant has been developed to meet the needs of modern transmission where higher efficiency is required. It is a low viscosity formulation that meets the more demanded OEM specifications.

Applications

- the latest generation of high efficiency 6/8-speed automatic transmission

Features and potential benefits

- Excellent viscosity stability in operation
- Exceptional friction and anti-shudder performances
- Enhanced fuel economies thanks to low viscosity and excellent low temperature performance
- Excellent thermal stability and resistance to oxidation.

Performance level

- GM Dexron VI, FORD Mercon LV, Chrysler MB236.12
- Mercedes Benz MB 236.12/14/15/41
- HYUNDAI KIA SP-IV/SP-H IV/SP-IV RR
- Mazda FZ, Mitsubishi ATF J-3, NISSAN Matic S, TOYOTA T-WS, JASO 1A, Honda DW-1
- ZF Lifeguardfluid 6/6 Plus/8

Typical Properties

Test Items	Method	Unit	Typical properties	
Specific gravity	ASTM D1298	-	0.846	
Color	ASTM D1500	-	Red	
Viscosity	40°C	ASTM D445	cSt	30.2
	100°C	ASTM D445	cSt	6.0
Viscosity index	ASTM D2270	-	153	
Flash point	ASTM D92	°C	215	
Pour point	ASTM D97	°C	-50	

S-OIL CORPORATION
192, Baekbeom-ro, Mapo-gu,
Seoul, 04196, Korea

S-OIL SEVEN ATF VI
2016.4.8.



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.