



# **Product Description**

S-OIL SEVEN BLUE1 CJ is made by 100% synthetic base oil, suitable for all heavy-duty engines, non turbo-charged or turbo-charged, in on and off-highway service. And recommended for vehicles fitted with after treatment devices including diesel particulate filters (DPFs)

## **Applications**

- O All turbocharged or normally aspirated diesel engines of vehicles operating in the most severe conditions
- O Light trucks, RVs, SUVs, Heavy trucks, Buses with diesel engines
- O Especially diesel vehicles with European engine under high pressure and temperature
- O Particularly suited for latest EURO VI to older generation engines fitted with after treatment devices including DPF, EGR and SCR

## Features and potential benefits

- O Full synthetic base oil enhance the engine protection and engine oil life thanks to high stability and cleanliness
- O This low SAPS (Sulfated Ash, phosphorus, sulfur) engine oil provides long life for exhaust after treatment devices including diesel particulate filter
- O Excellent detergent system helps keep pistons and other engine parts clean for long engine life
- O Good thermal breakdown resistance ensures engine protection under modern engine's severe conditions
- O In cold condition, Good fluidity provides easy start and prevents wear damage in initial stage

### **Performance level**

O ACEA: ACEA E9/E7 O Cummins: CES 20081

 O API : API CJ-4/SM
 O MAN : M3575

 O Mercedes-Benz : MB 228.31
 O MACK : EO-O PP

O Renault: RLD-3 O Caterpillar: ECF-3

### **Typical Properties**

<b>7</b> .	•				
Test Items		Method	Unit	10W-40	15W-40
Specific gravity		ASTM D1298	-	0.858	0.859
Viscosity	<b>40</b> ℃	ASTM D445	cSt	94.98	101.70
	100°C	ASTM D445	cSt	14.30	15.00
Viscosity index		ASTM D2270	-	154	154
Flash point		ASTM D92	$^{\circ}$	228	240
Pour point		ASTM D97	$^{\circ}$	-35	-32.5

S-OIL CORPORATION 192, Baekbeom-ro, Mapo-gu, Seoul, 04196, Korea

S-OIL SEVEN BLUE1 CJ 2017.6.7.





