



# S-OIL BRAKE FLUID DOT-4

## Class 4 Hydraulic Brake Fluid

### Applications

- S-OIL BRAKE FLUID DOT-4 is designed for use where a Class4 motor vehicle brake fluid is recommended by the motor vehicle manufacturer.

### Specifications

- S-OIL BRAKE FLUID DOT-4 meets and exceeds the requirements of the following specifications for DOT-4 brake fluid.
  - ISO 4925 (Class 4)
  - FMVSS 116
  - SAE J1704 (DOT-4)

### Storage

- S-OIL BRAKE FLUID DOT-4 should be stored in its original container until use. S-OIL BRAKE FLUID DOT-4 is hygroscopic by nature. Containers should be kept sealed to prevent the absorption of moisture.

### Typical Properties

Test Items	Unit	Results
Equilibrium Reflux Boiling Point		
Dry	°C / °F	262 / 500
Wet	°C / °F	173 / 320
Viscosity		
-40 °C	cst	1,100
100 °C	"	2.0
pH		8.0
Color		Amber

S-OIL CORPORATION  
192, Baekbeom-ro, Mapo-gu  
Seoul, 141096, Korea

S-OIL BRAKE FLUID DOT 4  
2017.09.14.



As even a high-quality oil selected for a particular application cannot exert its full performance unless machinery in use and/or applicable lubricant are not properly maintained, all potential problems can be prevented in advance if only lubricants in use are regularly analyzed.