



S-OIL BRAKE FLUID DOT-3

Class 3 Hydraulic Brake Fluid

Applications

- S-OIL BRAKE FLUID DOT-3 is designed for use where a Class3 motor vehicle brake fluid is recommended by the motor vehicle manufacturer.

Specifications

- S-OIL BRAKE FLUID DOT-3 meets and exceeds the requirements of the following specifications for DOT-3 brake fluid.
 - ISO 4925 (Class 3)
 - FMVSS 116
 - SAE J1704 (DOT-3)

Storage

- S-OIL BRAKE FLUID DOT-3 should be stored in its original container until use. S-OIL BRAKE FLUID DOT-3 is hygroscopic by nature. Containers should be kept sealed to prevent the absorption of moisture.

Typical Properties

Test Items	Unit	Results
Equilibrium Reflux Boiling Point		
Dry	°C / °F	240 / 464
Wet	°C / °F	146 / 295
Viscosity		
-40 °C	cst	1,300
100 °C	"	2.0
pH		8.8
Color		Amber

S-OIL CORPORATION
192, Baekbeom-ro, Mapo-gu
Seoul, 141096, Korea

S-OIL BRAKE FLUID DOT 3
2017.11.24.



As even a high-quality oil selected for a particular application cannot exert its full performance unless machinery in use and/or applicable lubricant are not properly maintained, all potential problems can be prevented in advance if only lubricants in use are regularly analyzed.