

# S-OIL GREASE LT

#### LOW TEMPERATURE LITHIUM GREASE

## **Applications**

- O S-OIL GREASE LT is made from mixed base oil and lithium soap thickener.
- O It has excellent performance of low temperature and water resistance.
- O S-OIL GREASE LT works well for automotive body lubrication where excellent low temperature performance is required.

#### **Advantages**

O Lubrication for automobile parts such as body, chassis, motor bearings and window regulator.

## **Specifications**

O -40 ~ 150 °C

#### **Characteristics**

Test Items	Method	Unit	No.2
NLGI grade	ASTM D-217		2
TEXTURE			Smooth
Color	ASTM D-1500		Pale Brown
Penetration, 25℃	ASTM D-217	0.1mm	281
Cooper corrosion, 100°C X 24hr	ASTM D-130		1a
Dropping point	IP 396/DIN ISO 2176	${\mathbb C}$	230

<sup>\*</sup> The typical characteristics are given as a guide only.

S-OIL CORPORATION 192, Baekbeom-ro, Mapo-gu Seoul, 04196, Korea

S-OIL GREASE LT 2016.12.23



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.