



CYLINDER LUBRICANT FOR 2-STROKE LOW SPEED DIESEL ENGINE

Product Description

S-OIL Marine CL 40 Series are superior, high-alkaline, cross-head engine oils, developed specifically for lubrication of modern, high output cross-head type engines using low Sulphur fuels(under 1.5wt%). S-OIL Marine CL 40 Series are formulated from high-quality base stocks with selected additives to provide optimum oxidation resistance at high temperatures. They also provide high levels of detergency, alkalinity and load-carrying ability to meet the performance requirements of modern cross-head type slow speed two stroke marine diesel engines.

Applications

O S-OIL Marine CL Series are recommended as a cylinder lubricant for all types of slow speed cross-head two stroke diesel

Features and potential benefits

- O Use strong alkali additives to prevents corrosion wear of the cylinder liners
- O High viscosity index maintain a strong film strength at high temperature
- O Outstanding detergency capability leads to cleaner piston rings and liners
- O Excellent thermal stability can lead to reduced carbon deposits and sludge formation

Performance level

O SAE 50

Typical Properties

SAE Grade			SAE 50
Test Items	Method	Unit	CL 4050
Specific gravity	ASTM D1298	-	0.9113
Viscosity 40°C	ASTM D445	cSt	220.2
100°C	ASTM D445	cSt	19.69
Viscosity index	ASTM D2270	-	102
Flash point	ASTM D92	°C	256
Pour point	ASTM D97	°C	-37.5
TBN	ASTM D2896		40

S-OIL CORPORATION 192, Baekbeom-ro, Mapo-gu, Seoul, 04196, Korea

S-OIL MARINE CL 2015.12.03.





