



S-OIL dragon SG

MULTIGRADE OIL FOR GASOLINE ENGINE OIL

Product Description

DRAGON SG is multi-grade engine oil for all gasoline engines. It suitable for recent technology engines (multi-valve, turbocharged, with/without catalytic converter) and vehicles requiring performance specification API SG

Applications

- All gasoline engines, especially for most recent technology engines (multi-valve, turbocharged, with/without catalytic converter) supercharged or not, in cars
- Suitable for all journeys (in town, on highways) and particularly in severe conditions
- For all driving styles, vigorous speeds in all seasons

Features and potential benefits

- Multi-grade
- Very high viscosity index
- Very good viscosity stability in operation
- Exceptional detergency level
- Exceptional soot dispersancy properties
- High performance level insures safer and longer drains intervals

Performance level

- API : API SJ(15W-40), SG

Typical Properties

Test Items	Method	Unit	15W-40	20W-50
Specific gravity	ASTM D1298	-	0.8726	0.8871
Viscosity	40°C ASTM D445	cSt	106.4	149.9
	100°C ASTM D445	cSt	14.93	17.25
Viscosity index	ASTM D2270	-	146	129
Flash point	ASTM D92	°C	228	238
H.T.H.S viscosity	ATSM D4683		3.83	4.6
Pour point	ASTM D97	°C	-35	-25

S-OIL CORPORATION
192, Baekbeom-ro, Mapo-gu,
Seoul, 04196, Korea

DRAGON SG
2016.12.13.



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.