

## **Product Description**

S-OIL SEVEN 4T RIDER #5 SG is multi grade engine oil specially designed for use in modern 4-stroke motorcycle. Its high viscosity index and purity provide excellent oxidation stability and cleanliness of engine.

### **Applications**

- O All type of modern 4-stroke motorcycle engines of all cubic capacities, for most severe condition of use
- O Adapted for gear boxes lubrication and oil immersed clutches

## **Features and Potential Benefits**

- O Very high viscosity index and good viscosity stability in operation
- O Exceptional detergency level and soot dispersion properties
- O High performance level insures safer and longer drains intervals

## **Performance Level**

O API : SG/CF-4

# **Typical Properties**

	Test Items	Method	Unit	15W-40
Specific Gravity		ASTM D1298	-	0.8761
Viscosity	<b>40</b> ℃	ASTM D445	cSt	111.6
	1 <b>00</b> ℃	ASTM D445	cSt	14.7
Viscosity Index		ASTM D2270	-	136
Flash Point		ASTM D92	°C	230
Pour Point		ASTM D97	°C	-35

S-OIL CORPORATION 192, Baekbeom-ro, Mapo-gu,	S-OIL SEVEN 4T RIDER #5 SG 2019.06.20	
Seoul, 04196, Korea		3 10349 SGS 1007 SGS 10 SGS

This lubricant used recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet is obtainable via your commercial adviser.