

# S-OIL SEVEN BLACK #9 LS 10W-40

Date of the previous version: 2019-06-19

Revision Date: 2019-06-19

Version 1

#### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name	S-OIL SEVEN BLACK #9 LS 10W-40
Pure substance/mixture	Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use

Diesel Engine Oil

#### 1.3. Details of the supplier of the safety data sheet

Supplier S-OIL CORPORATION 192, Baekbeom-ro, Mapo-gu, Seoul 04196, Korea

#### For further information, please contact:

Contact PointHSSEQE-mail Addressdolyoo@s-oil-total.com

#### 1.4. Emergency telephone number

Korea

+ 82 2 3772-5655

#### 2. HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

GHS Classification

#### 2.2. Label elements

GHS label elements, including precautionary statements

Symbol(s) Not Classified

Signal Words Not Classified

#### 2.3. GHS Hazard Statements

Not classified.

#### 2.4. GHS Precautionary Statements

Prevention	Not Classified
Response	Not Classified
Storage	Not Classified
Disposal	Not Classified



# S-OIL SEVEN BLACK #9 LS 10W-40

Date of the previous version: 2019-06-19

Revision Date: 2019-06-19

Version 1

#### 2.5. Other hazards

Physical-Chemical Properties

Contaminated surfaces will be extremely slippery.

**Environmental properties** 

Should not be released into the environment

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1. Mixture

Chemical Name	CAS-No	EC-No	Weight %
Severely hydrogenated heavy paraffinic distillate	64742-54-7	265-157-1	60.0 ~ 70.0
Mixed Performance Additive	-	-	20.0 ~ 25.0
Viscosity Modifier Additive	-		10.0 ~ 15.0

#### Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

#### 4. FIRST AID MEASURES

#### 4.1. Description of first-aid measures

General advice	IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.	
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids.	
Skin contact	Remove contaminated clothing and shoes. Wash skin with soap and water. Wash contaminated clothing before reuse. High pressure jets may cause skin damage. In this case, the casualty should be sent immediately to hospital.	
Inhalation	Move to fresh air.	
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.	
	s and effects, both acute and delayed	
4.2. Most important symptoms a	nd effects, both acute and delayed	
<u>4.2. Most important symptoms a</u> Eye contact	nd effects, both acute and delayed Not classified.	
Eye contact	Not classified. Not classified. High pressure injection of the products under the skin may have very serious consequences even though no symptom or injury may be	
Eye contact Skin contact	Not classified. Not classified. High pressure injection of the products under the skin may have very serious consequences even though no symptom or injury may be apparent. Not classified. Inhalation of vapors in high concentration may cause irritation of	

#### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

Treat symptomatically.



# S-OIL SEVEN BLACK #9 LS 10W-40

Date of the previous version: 2019-06-19

Revision Date: 2019-06-19

Version 1

#### 5. FIRE-FIGHTING MEASURES 5.1. Extinguishing media Suitable extinguishing media CO2, dry chemical, dry sand, alcohol-resistant foam. Unsuitable extinguishing media No information available 5.2. Special hazards arising from the substance or mixture **Special Hazard** Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These maybe highly dangerous if inhaled in confined spaces or at high concentration. 5.3. Advice for fire-fighters Special protective equipment for fire-Wear self-contained breathing apparatus and protective suit. fighters

#### 6. ACCIDENTAL RELEASE MEASURES

Other information

#### 6.1. Personal precautions, protective equipment and emergency procedures

t allow material to contaminate ground water system. Try to prevent the al from entering drains or water courses. authorities should be advised if significant spillages cannot be contained.
al from entering drains or water courses.
autornice chevia se autora il cigniliodri opilagos carnot se contairou.
nent and cleaning up
Ip. Contain spillage, and then collect with non-combustible absorbent al, (e.g.sand, earth, diatomaceous earth, vermiculite) and place in ner for disposal according to local / national regulations (see section 13). in suitable, closed containers for disposal.
ection 8 for more detail.
ection 13.

#### 7.1. Precautions for safe handling

Advice on safe handling

When using, do not eat, drink or smoke. For personal protection see section 8. Version GHS

Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.



# S-OIL SEVEN BLACK #9 LS 10W-40

Date of the previous version: 2019-0	6-19 <b>Revision Date:</b> 2019-06-19	Version
	Use only in well-ventilated areas. Do not breathe vapors or spray m contact with skin, eyes and clothing.	nist. Avoid
Prevention of fire and explosion	Take precautionary measures against static discharges. Ground/bc containers, tanks and transfer/receiving equipment.	ond
Hygiene measures	Ensure the application of strict rules of hygiene by the personnel ex- risk of contact with the product. Regular cleaning of equipment, wo clothing is recommended. Wash hands before breaks and immedia handling the product. Do not use abrasives, solvents or fuels. Do no with rags that have been contaminated with product. Do not put pro- contaminated rags into workwear pockets.	rk area and tely after ot dry hands
7.2. Conditions for safe stora	ge, including any incompatibilities	
Technical measures/Storage conditions	Keep away from food, drink and animal feedingstuffs. Keep in a burkeep container tightly closed. Keep preferably in the original contai Otherwise reproduce all indication of the regulation label on the new Do not remove the hazard labels of the containers (even if they are Design the installations in order to avoid accidental emissions of priseal breakage, for example) onto hot casings or electrical contacts. frost, heat and sunlight. Protect from moisture.	ner. v container. empty). oduct (due to
Materials to Avoid	Strong oxidizing agents.	
7.2 Specific and uses		
7.3. Specific end uses		
8. EXPOSURE CONTROLS/PE	RSONAL PROTECTION	
8. EXPOSURE CONTROLS/PE	RSONAL PROTECTION	
8. EXPOSURE CONTROLS/PE 8.1. Control parameters		
8. EXPOSURE CONTROLS/PE 8.1. Control parameters Exposure limits	oil mist : 10mg/m3, for 15 minutes; oil mist : 5mg/m3, for 8 hours	
8. EXPOSURE CONTROLS/PE 8.1. Control parameters		
8. EXPOSURE CONTROLS/PE 8.1. Control parameters Exposure limits	oil mist : 10mg/m3, for 15 minutes; oil mist : 5mg/m3, for 8 hours	
8. EXPOSURE CONTROLS/PE 8.1. Control parameters Exposure limits Legend	oil mist : 10mg/m3, for 15 minutes; oil mist : 5mg/m3, for 8 hours	
8. EXPOSURE CONTROLS/PE 8.1. Control parameters Exposure limits Legend 8.2. Exposure controls	oil mist : 10mg/m3, for 15 minutes; oil mist : 5mg/m3, for 8 hours	that there is
8. EXPOSURE CONTROLS/PE 8.1. Control parameters Exposure limits Legend 8.2. Exposure controls Occupational Exposure Controls	oil mist : 10mg/m <sub>3</sub> , for 15 minutes; oil mist : 5mg/m <sub>3</sub> , for 8 hours See section 16. Apply technical measures to comply with the occupational exposure When working in confined spaces (tanks, containers, etc.), ensure	that there is
8. EXPOSURE CONTROLS/PE   8.1. Control parameters   Exposure limits   Legend   8.2. Exposure controls   Occupational Exposure Controls   Engineering Measures   Personal Protective Equipment   General Information If	oil mist : 10mg/m <sub>3</sub> , for 15 minutes; oil mist : 5mg/m <sub>3</sub> , for 8 hours See section 16. Apply technical measures to comply with the occupational exposure When working in confined spaces (tanks, containers, etc.), ensure	that there is quipment. propriate
8. EXPOSURE CONTROLS/PE   8.1. Control parameters   Exposure limits   Legend   8.2. Exposure controls   Occupational Exposure Controls   Engineering Measures   Personal Protective Equipment   General Information If   p   Respiratory protection W   a (find the second	oil mist : 10mg/m <sub>3</sub> , for 15 minutes; oil mist : 5mg/m <sub>3</sub> , for 8 hours See section 16. Apply technical measures to comply with the occupational exposure When working in confined spaces (tanks, containers, etc.), ensure a supply of air suitable for breathing and wear the recommended er the product is used in mixtures, it is recommended that you contact the app rotective equipment suppliers. These recommendations apply to the	that there is quipment. propriate product as use /particulate
8. EXPOSURE CONTROLS/PE   8.1. Control parameters   Exposure limits   Legend   8.2. Exposure controls   Occupational Exposure Controls   Engineering Measures   Personal Protective Equipment   General Information If   p   Respiratory protection Waite and the second	oil mist : 10mg/m <sub>3</sub> , for 15 minutes; oil mist : 5mg/m <sub>3</sub> , for 8 hours See section 16. Apply technical measures to comply with the occupational exposure When working in confined spaces (tanks, containers, etc.), ensure t a supply of air suitable for breathing and wear the recommended ec the product is used in mixtures, it is recommended that you contact the app otective equipment suppliers. These recommendations apply to the upplied. /hen workers are facing concentrations above the exposure limit they must propriate certified respirators. Respirator with combination filter for vapour in 14387). The use of breathing apparatus must comply strictly with the material	that there is quipment. propriate product as use /particulate
8. EXPOSURE CONTROLS/PE   8.1. Control parameters   Exposure limits   Legend   8.2. Exposure controls   Occupational Exposure Controls   Engineering Measures   Personal Protective Equipment   General Information If   P   Respiratory protection Wait   If If   Eye Protection If	oil mist : 10mg/m <sub>3</sub> , for 15 minutes; oil mist : 5mg/m <sub>3</sub> , for 8 hours See section 16. Apply technical measures to comply with the occupational exposure When working in confined spaces (tanks, containers, etc.), ensure to a supply of air suitable for breathing and wear the recommended ex- the product is used in mixtures, it is recommended that you contact the approtective equipment suppliers. These recommendations apply to the upplied. When workers are facing concentrations above the exposure limit they must propriate certified respirators. Respirator with combination filter for vapour in 14387). The use of breathing apparatus must comply strictly with the ma structions and the regulations governing their choices and uses.	that there is quipment. product as use /particulate anufacturer's



# S-OIL SEVEN BLACK #9 LS 10W-40

Date of the previous version: 2019-06-19

Revision Date: 2019-06-19

Version 1

instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves.

#### Environmental exposure controls

**General Information** 

The product should not be allowed to enter drains, water courses or the soil.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. Information on basic physical and chemical properties

Color Physical State @20°C Odor		Yellow To amber liquid Characteristic	
Property	<u>Values</u>	Remarks	Method
pH Beiling peint/beiling serve		Not applicable	
Boiling point/boiling range Flash point	238 °C	Not applicable	Cleveland Open Cup (COC)
Evaporation rate		No information available	
Flammability Limits in Air		No information available	
Vapor Pressure		No information available	
Vapor density		No information available	
Density	860 kg/m₃	@ 15 °C	
Water solubility	Negligible	Insoluble	
Solubility in other solvents		No information available	
logPow		No information available	
Autoignition temperature	Not applicable		
Viscosity, kinematic	15.48 mm²/s	@ 100 °C	
Explosive properties	Not explosive		
Oxidizing Properties Possibility of hazardous reactions	Not applicable Not applicable		

#### 9.2. Other information

#### 10. STABILITY AND REACTIVITY

#### 10.1. Reactivity

**General Information** 

No information available.

#### 10.2. Chemical stability

Stability.

Stable under recommended storage conditions.

#### 10.3. Possibility of hazardous reactions

**Hazardous Reactions** 

None under normal processing.

#### 10.4. Conditions to Avoid

**Conditions to Avoid** 

Heat (temperatures above flash point), sparks, ignition points, flames, static electricity.

#### 10.5. Incompatible Materials



# S-OIL SEVEN BLACK #9 LS 10W-40

Date of the previous version: 2019-06-19

Revision Date: 2019-06-19

Version 1

Materials to Avoid Strong oxidizing agents.

#### **10.6. Hazardous Decomposition Products**

Hazardous Decomposition None under normal use. Product

#### **11. TOXICOLOGICAL INFORMATION**

#### 11.1. Information on toxicological effects

#### Acute toxicity Local effects Product Information

Skin contact	. Not classified. High pressure injection of the products under the skin may have very serious consequences even though no symptom or injury may be apparent.
Eye contact	. Not classified.
Inhalation	. Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	. Not classified.

#### Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Severely hydrogenated heavy paraffinic distillate	LD50 >5000mg/kg bw (Rat - OECD 401)	LD50 > 5000 mg/kg bw (Rabbit - OECD 402)	LC50 > 5mg/L (Rat (Aerosol)- OECD 403)
Mixed Performance Additive	LD50 >2000mg/kg (Rat - OECD 401) / LD50 >2000mg/kg (Rat - OECD 401) / LD50 2600mg/kg (Rat - OECD 401)	LD50 >2000mg/kg (Rat - OECD 402) / LD50 >2000mg/kg (Rat - OECD 402) / LD50 3160mg/kg (Rabbit - OECD 402)	LC50 > 2mg/L (1hr, Rat - OECD 403)

#### Sensitization

Sensitization	Not classified as a sensitizer.
Specific effects	
Carcinogenicity Mutagenicity Reproductive toxicity	This product is not classified carcinogenic. This product is not classified as mutagenic. This product does not present any known or suspected reproductive hazards.
Repeated Dose Toxicity	
Subchronic toxicity	No information available.
Target Organ Effects (STOT)	
Target Organ Effects (STOT)	No information available.
Other information	
Other adverse effects	Characteristic skin lesions (pimples) may develop following prolonged and repeated

Version GHS



# S-OIL SEVEN BLACK #9 LS 10W-40

Date of the previous version: 2019-06-19

Revision Date: 2019-06-19

Version 1

Page 7 / 9

exposures (contact with contaminated clothing).

#### **12. ECOLOGICAL INFORMATION**

#### 12.1. Toxicity

Acute aquatic toxicity - Product Information No information available.

#### Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates.	Toxicity to fish
Severely hydrogenated heavy paraffinic distillate	(48hr, Pseudokirchnerella	(48hr, Daphnia	LL50 > 100mg/L (96hr, Oncorhynchus mykiss - OECD 203)

#### **Chronic aquatic toxicity - Product Information**

No information available.

#### **Chronic aquatic toxicity - Component Information**

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates.	Toxicity to fish
Mixed Performance Additive	-	NOEL 10mg/L (21days, Daphnia magna - QSAR Petrotox)	NOEL > 1000mg/L (14/21days, Oncorhynchus mykiss - QSAR Petrotox)

Effects on terrestrial organisms

No information available.

#### 12.2. Persistence and degradability

**General Information** No information available. 12.3. Bioaccumulative potential **Product Information** No information available. logPow No information available **Component Information** No information available. 12.4. Mobility in soil Soil Given its physical and chemical characteristics, the product generally shows low soil mobility. Air Loss by evaporation is limited. Water Insoluble. The product spreads on the surface of the water. 12.5. Results of PBT and vPvB assessment PBT and vPvB assessment Not classified. 12.6. Other adverse effects **General Information** No information available



# S-OIL SEVEN BLACK #9 LS 10W-40

Date of the previous version: 2019-06-19

Revision Date: 2019-06-19

Version 1

Page 8 / 9

#### **13. DISPOSAL CONSIDERATIONS**

#### 13.1. Waste treatment methods

Waste from Residues / Unused Products	Should not be released into the environment. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.
EWC Waste Disposal No.	The following Waste Codes are only suggestions: 13 01 10. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.
14. TRANSPORT INFORMA	TION

ADR/RID	Not regulated			
IMDG/IMO	Not regulated			
ICAO/IATA	Not regulated			
ADN	Not regulated			

#### **15. REGULATORY INFORMATION**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Inventories

EINECS/ELINCS TSCA KECL Legend EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances TSCA - United States Toxic Substances Control Act Section 8(b) Inventory KECL - Korean Existing and Evaluated Chemical Substances

#### **Further information**

#### 15.2. Chemical Safety Assessment

Chemical Safety Assessment No information available

#### **16. OTHER INFORMATION**

#### Abbreviations, acronyms

Leaend Section 8

Logona boonon o		
+	Sensitizer	*
**	Hazard Designation	C:

Skin designation Carcinogen



### S-OIL SEVEN BLACK #9 LS 10W-40

Date of the previous version: 2019-06-19			Revision Date: 2019-06-19		Version 1
M:	Mutagen		R:	Toxic to reproduction	
Revision Date: Revision Note		2019-06-19 *** Indicates upo	dated section.		

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by theuser that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the safety data sheet