

MULTI GRADE OIL FOR DIESEL ENGINE

Product Description

S-OIL SEVEN BLUE #5 CD/SF is suitable to all turbocharged or normally aspirated diesel engines of civil works machines, trucks, fishing boats, locomotives and diesel stationary engines for energy production. It is also suitable for gearboxes, torque converters, hydraulic systems when manufacturers require engine oil with an appropriate grade for these applications.

Applications

O All turbocharged or normally aspirated diesel engines for all services when the manufacturer has no special requirement

Features and Potential Benefits

- O Very high viscosity index and good viscosity stability in operation
- O Excellent resistance of the oil film at high temperatures and resistance to oxidation
- O Very high level of detergency and dispersion properties
- O Very good anti-wear, anti-corrosion, anti-rust and anti-foaming properties

Performance Level

O API : CD/SF

Typical Properties

Test Items		Method	Unit	20W-50
Specific Gravity		ASTM D1298	-	0.882
Viscosity	40° C	ASTM D445	cSt	165.7
	100°C	ASTM D445	cSt	18.5
Viscosity Index		ASTM D2270	-	125
HTHS		ASTM D4683		4.80
Flash Point		ASTM D92	°C	250
Pour Point		ASTM D97	°C	-25

S-OIL CORPORATION 192, Baekbeom-ro, Mapo-gu, Seoul, 04196, Korea Seoul 2019.06.20	
--	--

This lubricant used recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet is obtainable via your commercial adviser.