



#### **MULTI GRADE OIL FOR GASOLINE ENGINE OIL**

### **Product Description**

S-OIL SEVEN RED #5 SG is multi grade engine oil for all gasoline engines. It suitable for recent technology engines (multi valve, turbocharged, with/without catalytic converter) and vehicles requiring performance specification API SG.

# **Applications**

- O All gasoline engines, especially for most recent technology engines (multi valve, turbocharged, with/without catalytic converter) supercharged or not, in cars
- O Suitable for all journeys (in town, on highways) and particularly in severe conditions
- For all driving styles, vigorous speeds in all seasons

#### **Features and Potential Benefits**

- O Very high viscosity index and good viscosity stability in operation
- O Exceptional detergency level and soot dispersion properties
- O High performance level insures safer and longer drains intervals

### **Performance Level**

O API: SG

# **Typical Properties**

Test Items		Method	Unit	15W-40	20W-50
Specific Gravity		ASTM D1298	-	0.8726	0.8871
Viscosity	<b>40</b> °C	ASTM D445	cSt	106.4	149.9
	100°C	ASTM D445	cSt	14.93	17.25
Viscosity Index		ASTM D2270	-	146	129
HTHS Viscosity		ASTM D4683	-	228	238
Flash Point		ASTM D92	$^{\circ}$	3.8	4.6
Pour Point		ASTM D97	°C	-35	-25

S-OIL CORPORATION 192, Baekbeom-ro, Mapo-gu, Seoul, 04196, Korea

S-OIL SEVEN RED #5 SG 2019.06.20







This lubricant used recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.