



# S-OIL SEVEN RED #5 SM

## MULTI GRADE OIL FOR GASOLINE ENGINE

### Product Description

S-OIL SEVEN RED #5 SM is multi grade engine oil for all gasoline engines. It suitable for recent technology engines (multi valve, turbocharged, with/without catalytic converter) and vehicles requiring performance specification API SM.

### Applications

- All gasoline engines, especially for most recent technology engines (multi valve, turbocharged, with/without catalytic converter) supercharged or not, in cars
- Suitable for all journeys (in town, on highways) and particularly in severe conditions
- For all driving styles, vigorous speeds in all seasons

### Features and Potential Benefits

- Meets API SM requirements, guarantee of an high and constant quality for lubricants
- Ensures easy cold start due to its extreme fluidity at low temperature and maintains a very resistant oil film even at extremely high operating temperature
- Protects mechanical parts and fully preserves the engine power, thus contributing to its youth and strength

### Performance Level

- API : SM/CF

### Typical Properties

| Test Items       | Method     | Unit | 10W-40 |
|------------------|------------|------|--------|
| Specific Gravity | ASTM D1298 | -    | 0.790  |
| Viscosity        | ASTM D445  | cSt  | 99.42  |
|                  | ASTM D445  | cSt  | 14.62  |
| Viscosity Index  | ASTM D2270 | -    | 153    |
| Flash Point      | ASTM D92   | °C   | 234    |
| Pour Point       | ASTM D97   | °C   | -38    |

S-OIL CORPORATION  
192, Baekbeom-ro, Mapo-gu,  
Seoul, 04196, Korea

S-OIL SEVEN RED #5 SM  
2019.06.20



This lubricant used recommended and for the application for which it has been designed does not present any particular risk.  
A material safety data sheet is obtainable via your commercial adviser.