



MULTI GRADE SYNTHETIC OIL FOR GASOLINE ENGINE

Product Description

S-OIL SEVEN RED #7 SL is made by synthetic technology for all gasoline engines. It suitable for recent technology engines (multi valve, turbocharged, with/without catalytic converter) and vehicles requiring performance specification API SL.

Applications

- O All gasoline engines, especially for most recent technology engines (multi valve, turbocharged, with/without catalytic converter) supercharged or not, in cars
- O Suitable for all journeys (in town, on highways) and particularly in severe conditions
- O For all driving styles, vigorous speeds in all seasons

Features and Potential Benefits

- O Meets API SL and ILSAC GF-3 requirements, guarantee of an high and constant quality for lubricants
- O Ensures easy cold start due to its extreme fluidity at low temperature and maintains a very resistant oil film even at extremely high operating temperature
- O Protects mechanical parts and fully preserves the engine power, thus contributing to its youth and strength

Performance Level

API : SL/CFILSAC : GF-3

Typical Properties

Test Items		Method	Unit	5W-30
Specific Gravity		ASTM D1298	-	0.8603
Viscosity	40 °C	ASTM D445	cSt	62.94
	100°C	ASTM D445	cSt	10.72
Viscosity Index		ASTM D2270	-	161
Flash Point		ASTM D92	$^{\circ}$	228
Pour Point		ASTM D97	$^{\circ}$	-40

S-OIL CORPORATION 192, Baekbeom-ro, Mapo-gu, Seoul, 04196, Korea

S-OIL SEVEN RED #7 SL 2019.06.20



This lubricant used recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.