



S-OIL SEVEN ATF III

MULTI-PURPOSE AUTOMATIC TRANSMISSION OIL

Product Description

S-OIL SEVEN ATF III is for automatic or semi-automatic transmissions and torque converters of all passenger cars, light commercial vehicles and industrial vehicles, when the manufacturer requires an automatic transmission fluid (ATF) GM DEXRON III.

Applications

- Suitable for use all transmissions of trucks, buses and public works machineries when a fluid type ALLISON C-4 is required
- Hydraulic systems when a fluid type GM DEXRON III is required

Features and Potential Benefits

- Very high viscosity index linked with an excellent viscosity stability in operation
- Very low pour point
- Excellent thermal stability and resistance to oxidation

Performance Level

- GM : DEXRON III H
- Ford : MERCON
- ALLISON : C-4/TES 389

Typical Properties

Test Items	Method	Unit	Properties
Specific Gravity	ASTM D1298	-	0.850
Viscosity	ASTM D445	cSt	35.1
	ASTM D445	cSt	7.48
Viscosity Index	ASTM D2270	-	228
Flash Point	ASTM D92	°C	188
Pour Point	ASTM D97	°C	-49
Brookfield Viscosity	ASTM D2983	cP	15,100

S-OIL CORPORATION
192, Baekbeom-ro, Mapo-gu,
Seoul, 04196, Korea

S-OIL SEVEN ATF III
2019.06.20



This lubricant used recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet is obtainable via your commercial adviser.