



S-OIL SEVEN ATF VI

FULLY SYNTHETIC AUTOMATIC TRANSMISSION FLUID

Product Description

S-OIL SEVEN ATF VI is an innovative automatic transmission fluid based on an advanced synthetic technology allowing very high performance. It offers fuel economies thanks to low viscosity. This lubricant has been developed to meet the needs of modern transmission where higher efficiency is required. It is a low viscosity formulation that meets the more demanded OEM specifications.

Applications

- The latest generation of high efficiency 6/8 speed automatic transmission

Features and Potential Benefits

- Excellent viscosity stability in operation
- Exceptional friction and anti-shudder performances
- Enhanced fuel economies thanks to low viscosity and excellent low temperature performance
- Good thermal stability and resistance to oxidation

Performance Level

- GM : DEXRON VI
- Ford : MERCON LV
- Chrysler : MB 236.12
- Mercedes Benz : MB 236.12/14/15/41
- Hyundai/Kia : SP-IV/SPH-IV/SP-IV-RR
- Mazda : ATF FZ
- Mitsubishi : ATF J-3
- Nissan MATIC S
- Toyota : T-WS
- JASO : 1A
- Honda : ATF DW-1
- ZF : LIFEGUARDFLUID 6/6 Plus/8

Typical Properties

Test Items	Method	Unit	Properties
Specific Gravity	ASTM D1298	-	0.846
Viscosity	ASTM D445	cSt	30.2
	ASTM D445	cSt	6.0
Viscosity Index	ASTM D2270	-	153
Flash Point	ASTM D92	°C	215
Pour Point	ASTM D97	°C	-50

S-OIL CORPORATION
192, Baekbeom-ro, Mapo-gu,
Seoul, 04196, Korea

S-OIL SEVEN ATF VI
2019.06.20



This lubricant used recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet is obtainable via your commercial adviser.