



S-OIL SEVEN BRAKE FLUID DOT-4

CLASS 4 HYDRAULIC BRAKE FLUIDS

Applications

- S-OIL SEVEN BRAKE FLUID DOT-4 is designed for use where a class 4 motor vehicle brake fluid is recommended by the motor vehicle manufacturer.

Specification

- Meets and exceeds the requirements of the following specifications for DOT-4 brake fluid
- ISO : 4925 (Class 4)
- NHTSA : FMVSS 116
- SAE : J1704 (DOT-4)

Storage

- S-OIL SEVEN BRAKE FLUID DOT-4 should be stored in its original container until use. This fluid is hygroscopic by nature. Containers should be kept sealed to prevent the absorption of moisture.

Typical Properties

	Test Items	Unit	Properties
Color		-	Amber
Viscosity	-40°C	cSt	1,100
	100°C	cSt	2.0
pH		-	8.0
Equilibrium Reflux Boiling Point	Dry	°C/°F	262/500
	Wet	°C/°F	173/320

S-OIL CORPORATION
192, Baekbeom-ro, Mapo-gu,
Seoul, 04196, Korea

S-OIL SEVEN BRAKE FLUID DOT-4
2019.06.20



This lubricant is recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet is obtainable via your commercial adviser.