



# S-OIL SEVEN BRAKE FLUID DOT-3

## CLASS 3 HYDRAULIC BRAKE FLUIDS

### Applications

- S-OIL SEVEN BRAKE FLUID DOT-3 is designed for use where a class 3 motor vehicle brake fluid is recommended by the motor vehicle manufacturer.

### Specification

- Meets and exceeds the requirements of the following specifications for DOT-3 brake fluid
- ISO : 4925 (Class 3)
- NHTSA : FMVSS 116
- SAE : J1704 (DOT-3)

### Storage

- S-OIL SEVEN BRAKE FLUID DOT-3 should be stored in its original container until use. This fluid is hygroscopic by nature. Containers should be kept sealed to prevent the absorption of moisture.

### Typical Properties

	Test Items		Unit	Properties
Color			-	Amber
Viscosity	-40°C		cSt	1,300
	100°C		cSt	2.0
pH			-	8.8
Equilibrium Reflux Boiling Point	Dry		°C/°F	240/464
	Wet		°C/°F	146/295

S-OIL CORPORATION  
192, Baekbeom-ro, Mapo-gu,  
Seoul, 04196, Korea

S-OIL SEVEN BRAKE FLUID DOT-3  
2019.06.20



This lubricant used recommended and for the application for which it has been designed does not present any particular risk.  
A material safety data sheet is obtainable via your commercial adviser.