

MATERIAL SAFETY DATA SHEET

S-OIL SEVEN GEAR TO-4 10W

Date of the previous version: 2018-03-14

Revision Date: 2018-03-14

Version 1

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product nameS-OIL SEVEN GEAR TO-4 10WPure substance/mixtureMixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use

Engine Oil.

1.3. Details of the supplier of the safety data sheet

Manufacturer

S-OIL CORPORATION 192, Baekbeom-ro, Mapo-gu, Seoul 04196, Korea

For further information, please contact:

Contact Point E-mail Address

1.4. Emergency telephone number

Korea

+82 2 3772 5655

2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification Serious eye damage/eye irritation : Category 2 Skin sensitization : Category 1





2.2. Label elements

Signal word

Warning

2.3. hazards Statement

H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H412	Harmful to aquatic life with long lasting effects
2.4. Precautionary Statements	

P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash the hands thoroughly after handling.



S-OIL SEVEN GEAR TO-4 10W

Date of the previous version: 2018-03-14	Revision Date: 2018-03-14 Ve		
P272 P273	Contaminated work clothing should not be allowed out of the Avoid release to the environment.	e workplace.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.		
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several m contact lenses, if present and easy to do. Continue rinsing.	ninutes. Remove	
P302+P352	IF ON SKIN: Wash with plenty of soap and water.		
P333+P313	If skin irritation or rash occurs: Get medical advice/attention		
P337+P313	If eye irritation persists: Get medical advice/attention.		
P308+P313	IF exposed or concerned: Get medical advice/attention.		
P321 P363	Specific treatment (see on this label). Wash contaminated clothing before reuse.		
1 300	wash containinated clothing before redse.		
P501	Dispose of contents/container to (in accordance with lo national / International regulation)	ocal / regional /	
2.5. Other hazards			
Physical-Chemical Properties	Contaminated surfaces will be extremely slippery.		
Environmental properties	Should not be released into the environment.		

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Mixture

Chemical Name	CAS-No	EC-No	Weight %
Severely hydrogenated heavy paraffinic distillate	64742-54-7	-	85.0 ~ 95.0
Mixed Performance Additive	Mixture	-	5.0 ~ 10.0
Pour point depressant	Mixture	-	< 1.0
Hazardous ingredients Do not contain hazardous substance nor substance with European workplace exposure limits in concentration above regulatory thresholds			
Additional information Proc 346	Product containing mineral oil with less than 3% DMSO extract as measured by IP 346		

4. FIRST AID MEASURES

4.1. Description of first-aid measures

General advice	IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids.
Skin contact	Remove contaminated clothing and shoes. Wash skin with soap and water. Wash contaminated clothing before reuse. High pressure jets may cause skin damage. In this case, the casualty should be sent immediately to hospital.
Inhalation	Move to fresh air.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.

4.2. Most important symptoms and effects, both acute and delayed



L MATERIAL SAFETY DATA SHEET

S-OIL SEVEN GEAR TO-4 10W

Date of the previous version: 201	8-03-14 Revision Date: 2018-03-14 Version 1		
Eye contact	Not classified.		
Skin contact	Not classified. High pressure injection of the products under the skin may have very serious consequences even though no symptom or injury may be apparent.		
Inhalation	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.		
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.		
4.3. Indication of immedia	te medical attention and special treatment needed, if necessary		
Notes to physician	Treat symptomatically.		
5. FIRE-FIGHTING MEASU	RES		
5.1. Extinguishing media			
Suitable extinguishing media	Carbon dioxide (CO 2). ABC powder. Foam. Water spray or fog.		
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire.		
5.2. Special hazards arisir	g from the substance or mixture		
Special Hazard	Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These maybe highly dangerous if inhaled in confined spaces or at high concentration.		
5.3. Advice for fire-fighter			
Special protective equipment for fire-fighters	Wear self-contained breathing apparatus and protective suit.		
Other information	Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.		
6. ACCIDENTAL RELEASE	MEASURES		
6.1. Personal precautions,	protective equipment and emergency procedures		
General Information	Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.		
6.2. Environmental precau	tions		
-			

6.3. Methods and material for containment and cleaning up

General Information

 Methods for containment
 Dam up. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

Do not allow material to contaminate ground water system. Try to prevent the material from courses. Local authorities should be advised if significant spillages cannot be contained.



L MATERIAL SAFETY DATA SHEET

S-OIL SEVEN GEAR TO-4 10W

Date of the previous version: 2018-03-14

Revision Date: 2018-03-14

Version 1

6.4. Reference to other sections

 Personal Protective Equipment
 See Section 8 for more detail.

 Waste treatment
 See section 13.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling	When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.
Prevention of fire and explosion	Take precautionary measures against static discharges. Ground/bond containers, tanks and transfer/receiving equipment.
Hygiene measures	Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.
7.2 Conditions for sofe sta	read including any incompatibilities

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage
conditionsKeep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep
container tightly closed. Keep preferably in the original container. Otherwise reproduce all
indication of the regulation label on the new container. Do not remove the hazard labels
of the containers (even if they are empty). Design the installations in order to avoid
accidental emissions of product (due to seal breakage, for example) onto hot casings or
electrical contacts. Protect from frost, heat and sunlight. Protect from moisture.Materials to AvoidStrong oxidizing agents.

7.3. Specific end uses

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters	
Exposure limits	Oil mist : TWA 5mg/m ³ (8hr), STEL 10mg/m ³ (15min).
Legend	See section 16.
8.2. Exposure controls	
Occupational Exposure Controls	
Engineering Measures	Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.
Personal Protective Equipment	
General Information	If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.



MATERIAL SAFETY DATA SHEET

S-OIL SEVEN GEAR TO-4 10W

Date of the previous version: 2018-03-14 Revision Date: 2018-03-14 Version 1 None under normal use conditions. When workers are facing concentrations above the **Respiratory protection** exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387). The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses. **Eye Protection** If splashes are likely to occur, wear:. Safety glasses with side-shields. Skin and body protection Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing. **Hand Protection** Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves. **Environmental exposure controls**

General Information

The product should not be allowed to enter drains, water courses or the soil.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Color Physical State @20°C Odor		Yellow to amber liquid Characteristic	
<u>Property</u> pH Boiling point/boiling range	<u>Values</u>	<u>Remarks</u> Not applicable Not applicable	<u>Method</u>
Flash point Evaporation rate Flammability Limits in Air Vapor Pressure Vapor density Density Water solubility Solubility in other solvents logPow Autoignition temperature	228 °C 881kg/m₃	No information available No information available No information available No information available @ 15 °C Soluble No information available No information available No information available	Cleveland Open Cup (COC)
Viscosity, kinematic Explosive properties Oxidizing Properties Possibility of hazardous reactions	38.43mm ² /s 6.237mm ² /s Not explosive Not applicable Not applicable	@ 40 °C @ 100 °C	
9.2 Other information			

9.2. Other information

Other Information

No information available.

10. STABILITY AND REACTIVITY

10.1. Reactivity

General Information

No information available.



-OIL MATERIAL SAFETY DATA SHEET

S-OIL SEVEN GEAR TO-4 10W

Date of the previous version: 2018-03-14

Revision Date: 2018-03-14

Version 1

10.2. Chemical stability

Stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous Reactions None under normal processing.

10.4. Conditions to Avoid

Conditions to Avoid Heat (temperatures above flash point), sparks, ignition points, flames, static electricity.)

10.5. Incompatible Materials

Materials to Avoid Strong oxidizing agents.

10.6. Hazardous Decomposition Products

Hazardous Decomposition	CO, CO ₂ , Carbon oxide.
Product	

11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity Local effects Product Information

Skin contact	. Not classified. High pressure injection of the products under the skin may have very serious consequences even though no symptom or injury may be apparent.
Eye contact	. Not classified.
Inhalation	. Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system
Ingestion	. Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Acute toxicity- Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Severely hydrogenated heavy	LD50 > 15000mg/kg	LD50 > 5000mg/kg	-
paraffinic distillate	(Rat)	(Rabbit)	

Sensitization

Chemical Name	Sensitization	
Mixed Performance Additive	Eye : Contact with the eyes causes permanent damage, including blindness. Symptoms may include pain, tearing, reddening, swelling and impaired vision. If this material is heated, thermal burns may result from eye contact.	
Mixed Performance Additive	Skin : Repeated contact with the skin may cause irritation. Symptoms may include pain, itching, discoloration, swelling, and blistering. Contact with the skin is not expected to cause an allergic skin response. Not expected to be harmful to internal organs if absorbed through the skin. If this material is heated, thermal burns may result from skin contact.	



-OIL MATERIAL SAFETY DATA SHEET

S-OIL SEVEN GEAR TO-4 10W

Date of the previous version: 2018-03-14

Revision Date: 2018-03-14

Version 1

Specific effects

Carcinogenicity	This product is not classified carcinogenic.
Mutagenicity	This product is not classified as mutagenic.
Reproductive toxicity	This product does not present any known or suspected reproductive hazards.

Chemical Name	Reproductive toxicity	
Mixed Performance Additive	Contains material that may cause adverse reproductive effects upon repeated swallowing based on animal data. The hazard evaluation is based on data for components or a similar material.	
Repeated Dose Toxicity		
Subchronic toxicity No information available.		
Target Organ Effects (STOT)		
Target Organ Effects (STOT)	information available.	
Other information		
ther adverse effects Characteristic skin lesions (pimples) may develop following prolonged and repe exposures (contact with contaminated clothing).		

12. ECOLOGICAL INFORMATION

12.1. Toxicity

Aquatic toxicity - Product Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates.	Toxicity to fish
Severely hydrogenated heavy paraffinic distillate	LC50 >1000mg/L 96hr	LC50 >1000mg/L 48hr	LC50 >1000mg/L 96hr

Effects on terrestrial organisms

No information available.

General Information

No information available.

12.2. Persistence and degradability

General Information

- Persistence No information available.
- degradability No information available.

General Information

No information available.

12.3. Bioaccumulative potential

Product Information

Chemical Name	Biodegradability
	• •



L MATERIAL SAFETY DATA SHEET

S-OIL SEVEN GEAR TO-4 10W

Date of the previous version: 2018-03-14

Revision Date: 2018-03-14

Version 1

Severely hydrogenated heavy paraffinic distillate 6% (28days)

<u>logPow</u>

12.4. Mobility in soil

Soil	Given its physical and chemical characteristics, the product generally shows low soil mobility.	
Air	Loss by evaporation is limited.	
Water	Soluble.	

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

12.6. Other adverse effects

General Information

No information available

13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues / Unused Products	Should not be released into the environment. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.	
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.	
EWC Waste Disposal No.	The following Waste Codes are only suggestions:. 13 01 10. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.	

14. TRANSPORT INFORMATION			
ADR/RID	Not regulated		
IMDG/IMO	Not regulated		
ICAO/IATA	Not regulated		
ADN	Not regulated		

15. REGULATORY INFORMATION

<u>15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture</u>

European Union

International Inventories



MATERIAL SAFETY DATA SHEET

S-OIL SEVEN GEAR TO-4 10W

Date of the previous version: 2018-03-14

Revision Date: 2018-03-14

Skin designation Trade secret

Carcinogen

Version 1

No information available

Further information

15.2. Chemical Safety Assessment

Chemical Safety Assessment No information available

16. OTHER INFORMATION

Abbreviations, acronyms

Legend Section 8

+	Sensitizer	*
**	Hazard Designation	*** :
M:	Mutagen	C:
Revision Date:	2018-03-14	

Revision Note *** Indicates updated section.

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by theuser that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the safety data sheet