S-OIL S-OIL SEVEN SUPER COOLANT LL

Product Description

S-OIL SEVEN SUPER COOLANT LL is the organic acid type of long life antifreeze and coolant with the change interval of 10 year or 200,000 km. This product is a nitrite-, borate-, phosphate-, silicate- and amine- free formulation. This meets the mixed specification of GM 6277M and SSANGYONG motor long life coolant.

Applications

- O Production line of car maker (SSANGYONG)
- O Industrial cooling system and vessel refrigerator system

Features and Potential Benefits

- O Superior protection in high operating temperatures
- O Do not cause precipitation by corrosion, mineral deposits and reaction hard water
- ${\bf O}~$ Outstanding hot surface aluminum protection
- O Excellent heat transfer properties

Freezing Temperature (Mixture Ratio)

Antifreeze, vol%	30	40	50	60
Water, vol%	70	60	50	40
Freezing Temp, ℃	-16	-26	-37	-52

Typical Properties

Test Items		Unit	Properties
Specific Gravity	20/20° ⊂	-	1.135
Boiling Point		°C	168
Freezing Point	50 vol% aqueous solution	°C	-37
	30 vol% aqueous solution	°C	-16
рН			8.2
Foaming		ml	0

S-OIL CORPORATION 192, Baekbeom-ro, Mapo-gu, Seoul, 04196, Korea	S-OIL SEVEN SUPER COOLANT LL 2019.06.20	
--	--	--

This lubricant used recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.