



# S-OIL SEVEN SUPER COOLANT

## ANTIFREEZE AND COOLANT

### Product Description

S-OIL SEVEN SUPER COOLANT is an antifreeze and coolant that is used by mixing with water in a certain ratio to cool gasoline and diesel engines as well as preventing them from freezing

### Applications

- Metal cooling systems such as casting, aluminum, steel and copper

### Features and Potential Benefits

- Superior anti-corrosion performance for metals
- It is chemically stable and prevents rust while not affecting the chamber and hose along with other chemical components which enhances the durability of the cooling system

### Freezing Temperature (Mixture Ratio)

Antifreeze, vol%	30	40	50	60
Water, vol%	70	60	50	40
Freezing Temp, °C	-16	-26	-37	-52

### Typical Properties

	Test Items	Unit	Properties
Specific Gravity	20/20°C	-	1.130
Boiling Point		°C	165
Freezing Point	50 vol% aqueous solution	°C	-37
	30 vol% aqueous solution	°C	-16
pH			7.7
Foaming		ml	0

S-OIL CORPORATION  
192, Baekbeom-ro, Mapo-gu,  
Seoul, 04196, Korea

S-OIL SEVEN SUPER COOLANT  
2019.06.20



This lubricant used recommended and for the application for which it has been designed does not present any particular risk.  
A material safety data sheet is obtainable via your commercial adviser.