



PREMIUM MULTI-FUNTIONAL UTTO FOR AGRICULTURUAL EQUIPMENT

Product Description

S-OIL 7 TRACTOR FLUID is designed for use in agricultural or off-road equipment fitted with transmissions, hydraulic systems and oil-immersed brakes requiring UTTO (Universal Tractor Transmission Oil). The performance meets the strict requirement of leading manufacturers including John Deere and New Holland etc.

Applications

- O Agricultural tractor transmission, hydraulic system and oil-immersed brake
- O Transmission fitted in off-road equipment requiring UTTO lubricants
- O Not to be used as an engine oil

Features and Potential Benefits

- O Optimized additive combination helps protecting gears and hydraulic component in equipment
- O Excellent extreme pressure and anti-wear characteristics provide reliable operation
- O Controls friction properties to ensure the smooth and comport operation of wet brake
- O Helps improving an efficiency of hydraulic system fitted in equipment
- O Outstanding oxidation and thermal stability prevent a formation of oxidation products, sludge and varnish
- O Shear stable oil maintains proper film thickness for oil's life

Performance Level

John Deere JDM J20C/D
Case
New Holland
Massey Ferguson

Typical Properties

Test Items		Method	Unit	Properties
Specific Gravity		ASTM D1298	-	0.8752
Viscosity	40 °C	ASTM D445	cSt	58.6
	100°C	ASTM D445	cSt	9.46
Viscosity Index		ASTM D2270	-	144
Flash Point		ASTM D92	$^{\circ}$ C	234
Pour Point		ASTM D97	$^{\circ}$ C	-38

S-OIL CORPORATION 192, Baekbeom-ro, Mapo-gu, Seoul, 04196, Korea

S-OIL SEVEN TRACTOR FLUID 2019.06.20



This lubricant used recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet is obtainable via your commercial adviser.