

S-OIL SEVEN RED #5 SL

MULTI GRADE OIL FOR GASOLINE ENGINE

Product Description

S-OIL SEVEN RED #5 SL is multi grade engine oil for all gasoline engines. It suitable for recent technology engines (multi valve, turbocharged, with/without catalytic converter) and vehicles requiring performance specification API SL.

Applications

- O All gasoline engines, especially for most recent technology engines (multi valve, turbocharged, with/without catalytic converter) supercharged or not, in cars
- O Suitable for all journeys (in town, on highways) and particularly in severe conditions
- $\ensuremath{\mathbb{O}}$ For all driving styles, vigorous speeds in all seasons

Features and Potential Benefits

- O Meets API SL requirements, guarantee of an high and constant quality for lubricants
- O Ensures easy cold start due to its extreme fluidity at low temperature and maintains a very resistant oil film even at extremely high operating temperature
- O Protects mechanical parts and fully preserves the engine power, thus contributing to its youth and strength

Performance Level

O API : SL/CF

Typical Properties

Т	est Items	Method	Unit	10W-40	20W-50
Specific Gravity		ASTM D1298	-	0.8692	0.8797
Viscosity	40° C	ASTM D445	cSt	106.9	169.9
	100°C	ASTM D445	cSt	15.88	19.16
Viscosity Index		ASTM D2270	-	159	128
Flash Point		ASTM D92	°C	222	248
Pour Point		ASTM D97	°C	-39	-28

S-OIL CORPORATION 192, Baekbeom-ro, Mapo-gu,	S-OIL SEVEN RED #5 SL 2019.06.20	
Seoul, 04196, Korea	2019.06.20	³⁷⁶³⁴⁹ SGS ³⁷⁰⁰⁷ SGS ³⁷³⁷⁸⁰⁰ SGS

This lubricant used recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.