Date of the previous version: 2018-03-14 Revision Date: 2018-03-14 Version 1

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name S-OIL SEVEN GEAR TO-4 40

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Engine Oil.

1.3. Details of the supplier of the safety data sheet

Manufacturer S-OIL CORPORATION

192, Baekbeom-ro, Mapo-gu,

Seoul 04196, Korea

For further information, please contact:

Contact Point E-mail Address

1.4. Emergency telephone number

Korea +82 2 3772 5655

2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification

Serious eye damage/eye irritation : Category 2

Skin sensitization: Category 1

Symbol(s)



2.2. Label elements

Signal word Warning

2.3. hazards Statement

H317 May cause an allergic skin reaction
H319 Causes serious eye irritation

H412 Harmful to aquatic life with long lasting effects

2.4. Precautionary Statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 Wash the hands thoroughly after handling.



Date of the previous version: 2018-03-14 Revision Date: 2018-03-14 Version 1

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P308+P313 IF exposed or concerned: Get medical advice/attention.

P321 Specific treatment (see ... on this label).
P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container to (in accordance with local / regional /

national / International regulation)

2.5. Other hazards

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.

Environmental properties Should not be released into the environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Mixture

Chemical Name	CAS-No	EC-No	Weight %
Severely hydrogenated heavy paraffinic distillate	64742-54-7	-	80.0 ~ 85.0
Residual oils (Petroleum), Hydrotreated	64742-57-0	-	10.0 ~ 15.0
Mixed Performance Additive	Mixture	-	5.0 ~ 10.0
Pour point depressant	Mixture	-	< 1.0

Hazardous ingredients Do not contain hazardous substance nor substance with European workplace

exposure limits in concentration above regulatory thresholds

Additional information Product containing mineral oil with less than 3% DMSO extract as measured by IP

346

4. FIRST AID MEASURES

4.1. Description of first-aid measures

General advice IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR

EMERGENCY MEDICAL CARE.

Eye contact Rinse thoroughly with plenty of water, also under the eyelids.

Skin contact Remove contaminated clothing and shoes. Wash skin with soap and water. Wash

contaminated clothing before reuse. High pressure jets may cause skin damage. In this

case, the casualty should be sent immediately to hospital.

Inhalation Move to fresh air.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Call a physician or Poison Control Center immediately.

4.2. Most important symptoms and effects, both acute and delayed

Date of the previous version: 2018-03-14 Revision Date: 2018-03-14 Version 1

Eye contact Not classified.

Skin contact Not classified. High pressure injection of the products under the skin may have very

serious consequences even though no symptom or injury may be apparent.

Inhalation Not classified. Inhalation of vapors in high concentration may cause irritation of

respiratory system.

Ingestion Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and

diarrhea.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media Carbon dioxide (CO 2). ABC powder. Foam. Water spray or fog.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Special Hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as

carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These maybe highly dangerous if inhaled in confined spaces or at high concentration.

5.3. Advice for fire-fighters

Special protective equipment for

fire-fighters

Wear self-contained breathing apparatus and protective suit.

Other information Cool containers / tanks with water spray. Fire residues and contaminated fire

extinguishing water must be disposed of in accordance with local regulations.

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely

slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all

sources of ignition.

6.2. Environmental precautions

General Information Do not allow material to contaminate ground water system. Try to prevent the material from

courses. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Methods for containment Dam up. Contain spillage, and then collect with non-combustible absorbent material, (e.g.

sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed

containers for disposal.

Date of the previous version: 2018-03-14 Revision Date: 2018-03-14 Version 1

6.4. Reference to other sections

Personal Protective Equipment See Section 8 for more detail.

Waste treatment See section 13.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling When using, do not eat, drink or smoke. For personal protection see section 8. Use only

in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin,

eyes and clothing.

Prevention of fire and explosion Take precautionary measures against static discharges. Ground/bond containers, tanks

and transfer/receiving equipment.

Hygiene measures Ensure the application of strict rules of hygiene by the personnel exposed to the risk of

contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture.

Materials to Avoid Strong oxidizing agents.

7.3. Specific end uses

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits Oil mist: TWA 5mg/m³(8hr), STEL 10mg/m³(15min).

Legend See section 16.

8.2. Exposure controls

Occupational Exposure Controls

Engineering Measures Apply technical measures to comply with the occupational exposure limits. When working

in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable

for breathing and wear the recommended equipment.

Personal Protective Equipment

General Information If the product is used in mixtures, it is recommended that you contact the appropriate

protective equipment suppliers. These recommendations apply to the product as

supplied.



MATERIAL SAFETY DATA SHEET

S-OIL SEVEN GEAR TO-4 40

Date of the previous version: 2018-03-14 Revision Date: 2018-03-14 Version 1

exposure limit they must use appropriate certified respirators. Respirator with

combination filter for vapour/particulate (EN 14387). The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their

choices and uses.

Eye Protection If splashes are likely to occur, wear:. Safety glasses with side-shields.

Skin and body protection Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing.

Hand Protection Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. Please observe the

instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the

supplier of the EC approved gloves.

Environmental exposure controls

General Information The product should not be allowed to enter drains, water courses or the soil.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Color Yellow to amber

Physical State @20°C liquid

Odor Characteristic

Property Values Remarks Method

Not applicable

Boiling point/boiling range Not applicable

Flash point 262 °C Cleveland Open Cup (COC)

Evaporation rateNo information availableFlammability Limits in AirNo information availableVapor PressureNo information available

Vapor Pressure No information available No information available

Density897kg/m3@ 15 °CWater solubilitySoluble

Solubility in other solvents

No information available

logPowNo information availableAutoignition temperatureNo information available

 Viscosity, kinematic
 144.5mm²/s
 @ 40 °C

 14.42 mm²/s
 @ 100 °C

Explosive properties Not explosive
Oxidizing Properties Not applicable
Possibility of hazardous reactions
Not applicable

9.2. Other information

Other Information No information available.

10. STABILITY AND REACTIVITY

10.1. Reactivity

General Information No information available.

Date of the previous version: 2018-03-14 Revision Date: 2018-03-14 Version 1

10.2. Chemical stability

Stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous Reactions None under normal processing.

10.4. Conditions to Avoid

Conditions to Avoid Heat (temperatures above flash point), sparks, ignition points, flames, static electricity.)

10.5. Incompatible Materials

Materials to Avoid Strong oxidizing agents.

10.6. Hazardous Decomposition Products

Hazardous Decomposition

Product

CO, CO₂, Carbon oxide.

11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity Local effects Product Information

Skin contact . Not classified. High pressure injection of the products under the skin may have very

serious consequences even though no symptom or injury may be apparent.

Eye contact . Not classified.

Inhalation . Not classified. Inhalation of vapors in high concentration may cause irritation of

respiratory system

Ingestion . Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and

diarrhea.

Acute toxicity- Component Information

		İ		
	Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
S	everely hydrogenated heavy	LD50 > 15000mg/kg	LD50 > 5000mg/kg	
p	araffinic distillate	(Rat)	(Rabbit)	-

Sensitization

Chemical Name	Sensitization
Mixed Performance Additive	Eye: Contact with the eyes causes permanent damage, including blindness. Symptoms may include pain, tearing, reddening, swelling and impaired vision. If this material is heated, thermal burns may result from eye contact.
Mixed Performance Additive	Skin: Repeated contact with the skin may cause irritation. Symptoms may include pain, itching, discoloration, swelling, and blistering. Contact with the skin is not expected to cause an allergic skin response. Not expected to be harmful to internal organs if absorbed through the skin. If this material is heated, thermal burns may result from skin contact.



MATERIAL SAFETY DATA SHEET

S-OIL SEVEN GEAR TO-4 40

Date of the previous version: 2018-03-14 Revision Date: 2018-03-14 Version 1

Specific effects

CarcinogenicityThis product is not classified carcinogenic.MutagenicityThis product is not classified as mutagenic.

Reproductive toxicityThis product does not present any known or suspected reproductive hazards.

Chemical Name	Reproductive toxicity
Mixed Performance Additive	Contains material that may cause adverse reproductive effects upon
	repeated swallowing based on animal data. The hazard evaluation is based
	on data for components or a similar material.

Repeated Dose Toxicity

Subchronic toxicity No information available.

Target Organ Effects (STOT)

Target Organ Effects (STOT) No information available.

Other information

Other adverse effects Characteristic skin lesions (pimples) may develop following prolonged and repeated

exposures (contact with contaminated clothing).

12. ECOLOGICAL INFORMATION

12.1. Toxicity

Aquatic toxicity - Product Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates.	Toxicity to fish
Severely hydrogenated heavy paraffinic distillate	LC50 >1000mg/L 96hr	LC50 >1000mg/L 48hr	LC50 >1000mg/L 96hr

Effects on terrestrial organisms

No information available.

General Information

No information available.

12.2. Persistence and degradability

General Information

Persistence No information available.

degradability No information available.

General Information

No information available.

12.3. Bioaccumulative potential

Product Information

1 TOGGOT INTO INIGUION		
Chemical Name	Biodegradability	



MATERIAL SAFETY DATA SHEET

S-OIL SEVEN GEAR TO-4 40

Date of the previous version: 2018-03-14 Revision Date: 2018-03-14 Version 1

Severely hydrogenated heavy paraffinic distillate

6% (28days)

<u>logPow</u>

12.4. Mobility in soil

Soil Given its physical and chemical characteristics, the product generally shows low soil

mobility.

Air Loss by evaporation is limited.

Water Soluble.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

12.6. Other adverse effects

General Information No information available

13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues / Unused

Products

Should not be released into the environment. Dispose of in accordance with the

European Directives on waste and hazardous waste. Dispose of in accordance with local

regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EWC Waste Disposal No. The following Waste Codes are only suggestions:. 13 01 10. According to the European

Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was

used.

14. TRANSPORT INFORMATION

ADR/RID Not regulated

IMDG/IMO Not regulated

ICAO/IATA Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

International Inventories

Date of the previous version: 2018-03-14 Revision Date: 2018-03-14 Version 1

No information available

Further information

15.2. Chemical Safety Assessment

Chemical Safety Assessment No information available

16. OTHER INFORMATION

Abbreviations, acronyms

Legend Section 8

+ Sensitizer * Skin designation
** Hazard Designation ***: Trade secret
M: C: Carcinogen

Revision Date: 2018-03-14

Revision Note *** Indicates updated section.

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by theuser that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the safety data sheet